


# Eurocode2 Design Guide for midas Gen


Integrated Design System for Building and General Structures






# Introduction

This design example book provides a comprehensive guide for RC design as per Eurocode2-1-1:2002. Specifically, this guide will review the design algorithms implemented in midas Gen, and go through design tutorials. This book is helpful in understanding the Eurocode design concept and verifying design results using midas Gen.




## CHAPTER 1 Why midas Gen

This chapter describes the main features and advantages of midas Gen and showcases prominent project applications.



## CHAPTER 2 RC Design Algorithms

This chapter discusses the general design concept of EN1992-1-1 and how it has been implemented in midas Gen. This enables the user to understand the equations, formulas, program limitations and development scope of the midas Gen design features.



## CHAPTER 3 RC Design Tutorial


This chapter enables the user to get acquainted with the RC design procedure in midas Gen as per EN1992-1-1: 2004. It encompasses the overall design procedure, from generating load combinations to checking design results with updated sections.





# Why midas Gen

Eurocode2 Design Guide for midas Gen





## CHAPTER 1

# Why midas Gen

### 01 Intuitive User Interface

The intuitive User Interface, contemporary Computer Graphics and substantially fast Solver Speed are some of the highlights of midas Gen. The user-oriented input/output features and significant analysis capabilities enable the practicing engineers and researchers to readily undertake structural analyses and designs for all types of buildings and even complex and long-span structures.

### 02 Advanced Analysis Features


midas Gen offers conventional analysis capabilities as well as other analyses such as Geometric Nonlinear Analysis reflecting Large Displacement, Boundary Nonlinear Analysis, Pushover Analysis, Construction Simulated Analysis reflecting time dependent material properties, Heat of Hydration Analysis, etc.

### 03 Accurate and Practical Results


Diverse ranges of specialty finite elements in conjunction with the latest theories of structural analyses render accurate and practical results. It is prominent for providing convenience, efficiency, versatility and productivity.

### 04 Design Capabilities


midas Gen provides design capabilities using various standards of different countries reflecting conventional as well as unusual design conditions, leading to Optimal Design. midas Gen has been used for over 20 years and applied to over an uncountable number of projects successfully, thereby, demonstrating its credibility and stability.




Multi-Use Complex



Moscow City by RMJM




Blast Furnace (Top Shell)



Burj Dubai

# midas Gen



Beijing Olympic Stadium

## Features

### Design Features

- **RC Design:**  
ACI318, Eurocode 2 & 8, BS8110, IS:456 & 13920, CSA-A23.3, GB50010, AIJ-WSD, TWN-USD, AIK-USD & WDS, KSCE-USD, KCI-USD
- **Steel Design:**  
AISC-ASD & LRFD, AISI-CFSD, Eurocode 3, BS5950, IS:800, CSA-S16, GBJ17 & GB50017, AIJ-ASD, TWN-ASD & LSD, AIK-ASD & LSD & CFSD, KSCE-ADS, KSSC-ASD
- **SRC Design:**  
SSRC, JGJ138, CECS28, AIJ-SRC, TWN-SRC, AIK-SRC2K, AIK-SRC, KSSC-CFT
- **Footing Design:** ACI381, BS8110
- **Slab & Wall Design:** Eurocode 2
- **Capacity Design:** Eurocode 8, NTC2008
- **General Section Designer:** P-M & M-M Interaction Surface, Moment Curvature Curve, Stress Contour

### Wind & Seismic Loads auto-generation

- **Wind Load:**  
IBC2000, UBC, ANSI, Eurocode 1, BS6399, IS875, NBC, GB, Japan, Taiwan & Korea
- **Seismic Load:**  
IBC2000, UBC, ATC 3-06, Eurocode 8, IS1893, NBC, GB, Japan, Taiwan & Korea

### High-rise Specific Functionality

- **3-D Column Shortening** reflecting change in modulus, creep and shrinkage
- **Construction Stage Analysis** accounting for change in geometry, supports and loadings
- **Building model generation wizard**
- Automatic mass conversion
- Material stiffness changes for **cracked sections**

### High-end Analysis Capabilities

- **P-Delta & Large Displacement Analysis**
- **Dynamic Analysis (Time History, Response Spectrum, etc.)**
- **Base Isolators & Dampers**
- **Pushover Analysis**
- **Inelastic Time History Analysis**
- **Staged post-tensioning**
- **Catenary Cable Structure**
- **Heat of Hydration Analysis**

### Intuitive User Interface

- **Works Tree** (Input summary with powerful modeling capabilities)
- Models created and changed with ease
- Floor Loads defined by areas and on inclined plane
- Built-in **Section Property Calculator**
- **Tekla Structures, Revit Structure & STAAD** interfaces

## Why midas Gen?

midas Gen is a Windows-based, **general-purpose** structural analysis and optimal design system.


The **intuitive user interface**, contemporary computer graphics and substantially fast **solver speed** are some of the highlights of midas Gen.

The user-oriented input/output features and significant analysis capabilities enable the **practicing engineers** and researchers to readily undertake structural **analysis and design** for even complex and large structures.


The fastest Multi-Frontal Solver and the latest analysis algorithms instantly bring accurate and practical analysis results.

In addition, midas Gen provides design capabilities using various standards of different countries leading to an **optimal design solution**.


## High-end Analysis Features




[ Construction Stage Analysis ]




[ Post-tension Analysis ]




[ Inelastic Time History Analysis ]



[ Pushover Analysis ]



[ Heat of Hydration Analysis ]




[ Detail Analysis ]




## Project Applications


### Specialty Structures




USA Pavilion (Shanghai EXPO)




German Pavilion (Shanghai EXPO)




Japan Pavilion (Shanghai EXPO)




Tempietto di Villa Barbaro (Italy)




Erdos Museum (Mongolia)




Maritime Museum (China)



Jeongdongjin Resort Facilities (Korea)




Saint Ignatius High School (Taiwan)



Sungsanpo Marine Terminal (Korea)

## Project Applications


### Buildings




Burj Khalifa (UAE)




Guangzhou Twin Tower (China)




Moscow City Palace (Russia)



Torre Eurosky (Italy)




Rolex Tower (UAE)



Taipei Twin Tower (Taiwan)



Hanoi Landmark (Vietnam)




Omnix Tower (UAE)




Gate of the Orient (China)

## Project Applications


### Plant Structures




Campiche Power Plant (Chile)



Nghi Power Plant (Vietnam)



Angamos Power Plant (Chile)



Hadeed CCL Steel Plant (Saudi Arabia)




TAVAZON Steel Plant (Iran)




India IISCO Steel Plant (India)



Pohang Steel Plant (Korea)



Zhangjiagang STS Steel Plant (China)





Gwangyang Steel Plant (Korea)




## Project Applications



### Spatial Structures




2008 Beijing Olympic Main Stadium (China)




2008 Beijing Olympic Basketball Arena (China)




2008 Beijing Olympic Badminton Arena (China)




FIFA World Cup Main Stadium (Korea)




FIFA World Cup Daejeon Stadium (Korea)




FIFA World Cup Jeonju Stadium (Korea)



Incheon International Airport (Korea)



Beijing International Airport (China)




Seoksan Subway Station (Korea)



# RC Design Algorithm

Eurocode2 Design Guide for midas Gen





**Overview**

1.1 Design Scope .....	3
1.2 Materials .....	3
1.2.1 Concrete .....	3
1.2.1.1 Modulus of Elasticity ( $E_c$ ).....	4
1.2.1.2 Poisson's Ratio .....	4
1.2.1.3 Weight Density .....	4
1.2.1.4 User Defined Materials .....	5
1.2.2 Reinforcement .....	5
1.2.2.1 Modulus of Elasticity ( $E_s$ ).....	6
1.2.3 Design Strength of Materials .....	6
1.2.3.1 Design compressive strength of concrete ( $f_{cd}$ ) .....	6
1.2.3.2 Design yield strength of reinforcement ( $f_{yd}$ ) .....	6
1.2.3.3 Short/Long Term Elasticity Ratio.....	7
1.2.3.4 Partial Safety Factors for Materials.....	8
1.3 Design Information .....	9
1.3.1 Member Assignment .....	9
1.3.2 Unbraced Length .....	10
1.3.3 Live Load Reduction Factor .....	10
1.3.4 Imperfections.....	11
1.3.5 P-Delta Analysis .....	11
1.3.6 Pattern Loading .....	12
1.3.7 Selection of Design Code .....	12

**Ultimate Limit State**

2.1 Design for flexure without axial force .....	13
2.1.1 Requirements .....	13
2.1.2 Calculating the moment capacity, $M_{Rd}$ .....	13
2.1.3 Design Criteria for Rebars.....	16
2.1.4 Concrete Checking for beams .....	17
2.1.4.1 Rebar Input for Beam Checking .....	18
2.1.5 Design load combinations .....	18
2.2 Design for flexure with Axial Force .....	19
2.2.1 Requirements .....	19
2.2.2 Magnification of Design Moments .....	19
2.2.2.1 Slenderness ratio.....	19
2.2.2.2 Limiting value of slenderness ratio.....	20
2.2.2.3 Magnification of Moments .....	21
2.2.3 Determination of the Eccentric Axial Load Capacity.....	22
2.2.4 Design Criteria for Rebars.....	26
2.2.5 Concrete checking for columns & walls .....	26
2.2.5.1 Rebar Input for Column Checking .....	26
2.2.5.2 Rebar Input for Wall Checking.....	27
2.2.6 Design load combinations .....	27
2.3 Design for Shear.....	28
2.3.1 Requirements .....	28
2.3.2 Calculation of Shear Resistance ( $V_{Rd}$ ) .....	28
2.3.2.1 Members not requiring design shear reinforcement .....	28
2.3.2.2 Members requiring design shear reinforcement .....	28
2.3.3 Design Criteria for Rebars.....	30
2.3.4 Shear in Concrete Code Checking .....	31
2.3.5 Design Load Combinations .....	31

2.4 Verification of Design/Check Results -----	31
2.4.1 Design Result Dialog box.....	31
2.4.2 Design/Check Reports .....	31
<b>Serviceability Limit State</b>	
3.1 Serviceability Type Load Combination-----	34
3.1.1 Definition of Short Term and Long Term Load .....	34
3.1.2 Classification of Serviceability type Load Combinations.....	34
3.2 Serviceability Parameters-----	35
3.3 Stress Limitation-----	36
3.3.1 Stress Verification to avoid micro cracking.....	36
3.3.1.1 Un-cracked Sections-----	36
3.3.1.2 Cracked Sections -----	37
3.3.2 Check for linear Creep .....	38
3.3.2.1 Uncracked Sections-----	38
3.3.2.2 Cracked sections-----	38
3.4 Crack width -----	38
3.4.1 Calculate crack widths.....	38
3.4.2 Limiting Crack Width, $w_{max}$ .....	39
3.4.2.1 Exposure Class -----	40
3.5 Deflection Check-----	40
3.6 Verification of Results-----	40
3.6.1 Check Result dialog box .....	40
3.6.2 Design/Check Reports .....	40
<b>Detailing Rules</b>	
4.1 Detailing rules for Beam Design -----	42
4.1.1 Longitudinal Reinforcement.....	42
4.1.2 Shear Reinforcement.....	42
4.2 Detailing Rules for column design-----	43
4.2.1 Longitudinal Reinforcement.....	43
4.2.2 Shear Reinforcement.....	43
4.3 Detailing Rules for Wall design -----	44
4.3.1 Vertical Reinforcement .....	44
4.3.2 Horizontal Reinforcement .....	44

# Overview

## 1.1 Design Scope

midas Gen provides automatic design of concrete beam, column, shear wall, meshed slab and meshed wall. The program also supports section checking when relevant data is specified. With respect to Eurocode, the major capabilities of the program can be summarized as below:

- Ultimate Limit State and Serviceability Limit State design and checking
- Auto generation of load combinations as per Eurocode 1990:2002
- Auto generation of Static Wind Loads as per Eurocode 1991-1-4:2005
- Auto generation of Static Seismic Loads & Response Spectrum Functions as per Eurocode 1998-1:2004
- Capacity design as per Eurocode 1998-1:2004
- Available Section shapes for design:
  - Beam: Rectangle, T-shape
  - Column: Rectangle, Circular, Hollow circular
  - Wall: Rectangle
- Design and checking of meshed slab and meshed wall
- Cracked section analysis of slabs for serviceability checks

The following should be taken care of by the user:

- Torsion check is not provided by midas Gen.
- Irregular wall such as L or H shape cannot be designed.
- Isolated footing design is not supported as per EN 1992-1-1:2004.

This design guide covers the design of frame elements as per EN 1992-1-1:2004 for non-seismic situations. Aspects of column design, beam design and wall design are discussed in this guide.

For the purpose of component design, midas Gen interacts with midas Design+. midas Design+ is a collection of handy structural component design and detailing tools, which are easy to use and speed up the day-to-day design process. midas Design+ is developed to be simple, fast and accurate. It enables engineers to systematically and consistently manage design reports. midas Design+ supports Column design, Wall Design and Strip Footing Design as per Eurocode.

[Table 1.1] Capabilities of midas Gen with respect to Eurocode

	Ultimate Limit State				Serviceability Limit State		
	Flexure	Shear	Axial	Torsion	Stress	Deflection	Crack Control
Beam	✓	✓			✓	✓	✓
Column	✓	✓	✓		✓		
Wall	✓	✓	✓				
Meshed Slab	✓	✓			✓	✓	✓
Meshed Wall	✓	✓	✓				

## 1.2 Materials

### 1.2.1 Concrete

EN 1992-1-1:2004 (Table 3.1) provides specifications about strength and deformation characteristics of concrete. midas Gen supports a material database as per the specifications. Any of the materials can be easily chosen for analysis as well as design. The following are the strength classes of concrete

as identified by the code:

- C12/15
- C16/20
- C20/25
- C30/37
- C35/45
- C40/50
- C45/55
- C50/60
- C55/67
- C60/75
- C70/85
- C80/95
- C90/105

Material name C40/50 implies that the cylinder characteristic strength ( $f_{ck}$ ) at 28 days is 40 MPa and cube characteristic strength ( $f_{ck,cube}$ ) at 28 days is 50 MPa.

The material can be chosen in **Material Data** dialog Box as shown below. In dialog box, choose **Type of Design** as “Concrete”. **Standard** as “EN04(RC)”. Then from DB drop down list any of the above materials can be chosen.

### 1.2.1.1 Modulus of Elasticity ( $E_c$ )

For materials selected from EN 1992-1-1:2004, the modulus of elasticity is obtained using the formula as specified by the code:

$$E_{cm} = 22 \left( \frac{f_{cm}}{10} \right)^{0.3} \quad (1.1)$$

$$f_{cm} = f_{ck} + 8 \text{ (MPa)} \quad (1.2)$$

EN1992-1-1:2004  
Table 3.1

#### Note for Italian users

*For Italian user, the program supports the UNI material database. The database includes the following materials:*

- Rck 10
- Rck 15
- Rck 20
- Rck 25
- Rck 30
- Rck 35
- Rck 40
- Rck 45
- Rck 50.

*For these materials, the user needs to choose the Standard as “UNI(RC)” and then select the desired material.*

### 1.2.1.2 Poisson's Ratio

The default value of Poisson's ratio is used as 0.2. For a different value of Poisson's ratio user defined material needs to be specified as per Section 1.2.1.4 of this guide.

### 1.2.1.3 Weight Density

The weight density is used as 25 kN/m<sup>3</sup> for all the material from the database. For a different weight density user defined material needs to be specified as per Section 1.2.1.4 of this guide.

❖ *Model > Properties > Material*

The Material Data dialog box is shown with the following fields:

- General:** Material ID: 1, Name: C40/50
- Elasticity Data:** Type of Design: Concrete, Type of Material: Isotropic (selected), Orthotropic (unselected)
- Steel:** Standard: (empty), DB: (empty)
- Concrete:** Standard: EN04(RC), Code: C40/50, DB: C40/50
- Steel Properties:** Modulus of Elasticity: 0.0000e+000 N/mm², Poisson's Ratio: 0, Thermal Coefficient: 0.0000e+000 1/[F], Weight Density: 0 N/mm³, Use Mass Density: 0 N/mm³/q
- Concrete Properties:** Modulus of Elasticity: 3.5220e+004 N/mm², Poisson's Ratio: 0.2, Thermal Coefficient: 5.5556e-006 1/[F], Weight Density: 2.5e-005 N/mm³, Use Mass Density: 2.549e-009 N/mm³/q
- Plasticity Data:** Plastic Material Name: NONE
- Thermal Transfer:** Specific Heat: 0 Btu/N·[F], Heat Conduction: 0 Btu/mm·hr·[F], Damping Ratio: 0.05

[Figure 1.1] Material Data dialog box

**1.2.1.4 User Defined Materials**

User defined Concrete Material can be specified. **Type of Design** should be used as **Concrete**, otherwise the design cannot be performed for the specified material. Then select the **Standard** as **None** to input the user defined material properties. Type of design should not be selected as User Defined.

**1.2.2 Reinforcement**

The reinforcement material can be specified in **Modify Concrete Materials** dialog box as shown in Section 1.2.3. If the material is not specified there, then the default material will be taken as specified in **Design/Load Code Environment** in **Tools > Preferences**. Then under Concrete heading user can specify the database for Rebar. The available rebar materials as per Eurocode are as follow:

[Table 1.2] Available Rebar Materials as per EN 1992-1-1:2004

Rebar Material	Yield Strength ( $f_y$ ) (MPa)
<b>Class A</b>	400
<b>Class B</b>	500
<b>Class C</b>	600


**Note for Italian users**

For Italian users, the program supports the UNI database consisting of the following materials:

- FeB22k
- FeB32k
- FeB38k
- FeB44k

To select the above materials, we need to specify the Material Code as “UNI(RC)”.

## ❖ Tools &gt; Preferences



[Figure 1.2] Preferences dialog box

**1.2.2.1 Modulus of Elasticity ( $E_s$ )**

For all the reinforcing materials, modulus of elasticity is used as 200 GPa. Different value of Modulus of Elasticity cannot be specified for reinforcing materials.

**1.2.3 Design Strength of Materials****1.2.3.1 Design compressive strength of concrete ( $f_{cd}$ )**

The code specifies the following equation for the calculation of the design compressive strength:

$$f_{cd} = \frac{\alpha_{cc} f_{ck}}{\gamma_c} \quad (1.3)$$

where,

$f_{ck}$ : If standard material is used, the value is taken automatically as specified in the code. For a user defined material, we need to specify the  $f_{ck}$  in **Modify Concrete Materials** dialog box shown below.

$\alpha_{cc}$ : Coefficient to account for:

1. Long term effects on the compressive strength
2. Unfavorable effects resulting from the way the load is applied.

It can be specified in the **Partial Safety Factor for Materials** dialog box as shown in Section 1.2.3.4.

$\gamma_c$ : The partial safety factor for concrete. It depends on the design situation. It can be specified in the **Partial Safety Factor for Materials** dialog box as shown in Section 1.2.3.4.

**1.2.3.2 Design yield strength of reinforcement ( $f_{yd}$ )**

The yield strength specified for reinforcing material will be used to calculate the design yield strength as per the following specification of code:

$$f_{yd} = \frac{f_{yk}}{\gamma_s} \quad (1.4)$$

where,

$f_{yk}$ : The characteristic yield strength of reinforcement.

$\gamma_s$ : The partial safety factor for steel. It depends on the design situation. It can be specified in the **Partial Safety Factor for Materials** dialog box as shown in Section 1.2.3.4.

EN1992-1-  
1:2004  
3.1.6(1)

EN1992-1-  
1:2004  
3.1.6(2)



❖ *Design > Concrete Design Parameter > Modify Concrete Materials*

ID	Name	fcd/fck/R	Chk	Lambda	Main-bar	Sub-bar
1	C30/37	30	X	1	Class B	Class A

Concrete Material Selection

Code :  Name :  ...

Specified Compressive Strength (fcd/fck) :  N/mm<sup>2</sup>

☐ Light Weight Concrete Factor (Lambda) :

Rebar Selection

Code :

Grade of Main Rebar :  Fy :  N/mm<sup>2</sup>

Grade of Sub-Rebar :  Fys :  N/mm<sup>2</sup>

[Figure 1.3(a)] Modify Concrete Material dialog box

In the above dialog box, the concrete and rebar material properties can be specified for design.

If standard material is used, the value is taken as specified in the code. In that case, this step is not a mandatory step. If material is user defined, then select '**None**' in the **Code** field and enter the name of material to be used in the Name field. Then, each data field is activated and the strength of materials can be entered.

Lightweight Concrete Factor (Lambda): This is irrelevant for design as per Eurocode.

Grade of Main Rebar: The material specified here will be used for the longitudinal reinforcement.

Grade of Sub Rebar: The material specified here will be used for the stirrups.

❖ *Design > Concrete Design Parameter > Modify Concrete Materials> ...*

Short/Long Term Elasticity Ratio

Ratio of Modulus of Elasticity

n (Short Term) :

n (Long Term) :

[Figure 1.3(b)] Short/Long Term Elasticity Ratio dialog box

### 1.2.3.3 Short/Long Term Elasticity Ratio

For serviceability check as per Eurocode 2, the ratios of the modulus of elasticity of reinforcement to the modulus of elasticity of concrete for short-term and long term can be entered.

The default value for short-term ratio is  $E_s/E_c$  and  $2(E_s/E_c)$  for long-term ratio.

The ratio can be edited in the **Modify Concrete Materials** Dialog Box. The button next to the Name field, provides access to the **Short/Long Term Elasticity Ratio** dialog box.

### 1.2.3.4 Partial Safety Factors for Materials

❖ Design > Concrete Design Parameter > Partial Safety Factors for Material Properties

[Figure 1.4 Partial Factors for Material Properties dialog box]

[Table 1.3] Recommended Values of Partial Safety Factors for Materials

Design Situations	$\gamma_c$	$\gamma_s$
<b>Persistent &amp; Transient</b>	1.5	1.15
<b>Accidental</b>	1.2	1.0

As per EN1990:2002, design situations are classified as:

- a. Fundamental Design Situations:
  1. Persistent Design Situations  
Relevant during design working life of structure
  2. Transient Design Situation  
Relevant for a shorter duration. eg: execution or repair
- b. Seismic Design Situation  
Relevant during the earthquake
- c. Accidental Design Situation  
Exceptional conditions like fire events, explosions, blast etc.

Specification 5.2.4(2) of EN1998-1:2004 "If more specific data are not available, the values of the partial factors  $\gamma_c$  and  $\gamma_s$  adopted for the persistent and transient design situations should be applied". midas Gen uses the same values of  $\gamma_c$  and  $\gamma_s$  for all three design situations i.e Persistent, Transient & Seismic Design Situations.


The design situation is identified automatically by the program as per the following table:

[Table 1.4] Classification of Design Situations

Design situations	Description
Fundamental and Seismic	Load combinations not covered in "Accidental Situation"
Accidental	Load Combination including any of the following type of load case, will be classified in Accidental Situation: Live Load Impact (IL) Collision Load (CO)

Load Case type is specified in the dialog box below:

## ❖ Load &gt; Static Load Cases



[Figure 1.5] Static Load Cases dialog box


After identifying the design situation respective partial safety factors for materials are used by the program in design.

## 1.3 Design Information

### 1.3.1 Member Assignment

The program offers to consider a number of line elements as a single member for the purpose of design. The design forces and the section capacities will be calculated at the  $i$ ,  $\frac{1}{4}$ ,  $\frac{1}{2}$ ,  $\frac{3}{4}$ ,  $j$ -point of the member and not of the element. Also, the span for the design will be considered as per the specifications of the member and not of the element.

The unbraced length will be taken on a member basis, instead of element basis. Laterally Unbraced Length is taken from the member.



Unbraced length of a column ② :  $L_y = L2$ ,  $L_z = L1$

Unbraced length of a column ③ :  $L_y = L3$ ,  $L_z = L1$


Unbraced length of a column ④ :  $L_y = L_z = L1$

[Figure 1.6] Unbraced Length for column

If the elements to be assigned to a member retain different material and section properties, or the

directions of the node connections are different, a member cannot be assigned.

❖ *Design > General Design Parameter > Member Assignment*



[Figure 1.7 Member Assignment dialog box]


### 1.3.2 Unbraced Length

When members are defined by Member Assignment, unbraced lengths about the member's strong axis (y-Axis) and weak axis (z-Axis) are automatically calculated by the program considering the connectivity of the members.

If members are not defined then the unbraced length is taken equal to the length of the element for bending about both axis.

The unbraced length can also be specified by the user in **Unbraced Length** dialog box as shown below. If unbraced length is specified as 0, then program will take the unbraced length as the length of the member or the length of the element, whichever is applicable.

❖ *Design > General Design Parameter > Unbraced Length*




[Figure 1.8] Unbraced Length dialog box

### 1.3.3 Live Load Reduction Factor

When calculating the Forces for design, the effect of live load can be reduced. Axial force, moments and shear forces due to actions can be reduced. The reduction factor can be specified in the Modify Live Load Reduction Factor dialog box. In order to specify the live load to be reduced to 80%, the factor of 0.8 should be added for the respective forces.

## ❖ Design &gt; General Design Parameters &gt; Modify Live Load Reduction Factor



[Figure 1.9 Modify Live Load Reduction Factor dialog box]

The live load reduction factor needs to be calculated manually. The formula specified by EN 1991-1-1:2002 is:

$$\alpha_n = \frac{2 + (n+2)\psi_0}{n} \quad (1.5)$$

where:

$n$  is the number of storeys ( $>2$ ) above the loaded structural elements from the same category.

$\psi_0$  is the factor for combination of variable actions. It is provided in EN 1990, Annex A1, Table A1.1.

EN 1991-1-1:2002  
6.3.1.2(11)

### 1.3.4 Imperfections


Eurocode 1992-1-1:2004 specifies that the unfavorable effects of possible deviations in the geometry of the structure and the position of loads shall be taken into account in the analysis of members and structures. The imperfections should be modelled manually by the user.

In order to consider the effect of these imperfections, the code provides equivalent transverse forces for these imperfections in Section 5.2 using equations from 5.4 to equation 5.6. These forces need to be calculated and applied manually by the user.

### 1.3.5 P-Delta Analysis

The amplification of the moments due to second order effects is specified by the code. Second order effects due to both the change of geometry of structure (P- $\Delta$ ) and the curvature of member (P- $\delta$ ) need to be considered.

The second order effects can be easily considered in the program by performing P-Delta Analysis. The program performs both P- $\Delta$  as well as P- $\delta$  analysis. The corresponding magnified moments can be used for the design of the members. In case the P-delta analysis is not performed, the provisions of code will be used to obtain the second order moments. The method of moment magnification as per Eurocode 2 will be discussed in Section 2.2.

❖ *Analysis > P-Delta Analysis Control*


[Figure 1.10] P-Delta Analysis Control dialog box

**1.3.6 Pattern Loading**

At the moment, the program doesn't support the auto generation of the pattern load combinations.

**1.3.7 Selection of Design Code**

The design code can be selected in the Concrete Design Code dialog box as shown below:

❖ *Design > Concrete Design Parameters > Concrete Design Code*

[Figure 1.11] Concrete Design Code dialog box

In addition to the recommended values, the program supports the following National Annexes for design:

- Italy
- Sweden
- Singapore

# Ultimate Limit State

## 2.1 Design for flexure without axial force

### 2.1.1 Requirements


Moment capacity of the section ( $M_{Rd}$ ) should be greater than the design moment for the section ( $M_{Ed}$ ).

To satisfy limit state of moment resistance the following condition should be met:

$$M_{Ed} \leq M_{Rd}$$

### 2.1.2 Calculating the moment capacity, $M_{Rd}$

The distribution of strain and stresses in the section is as follows:



[Figure 2.1] Distribution of strain and stresses in the section

where,


$\lambda$ : factor defining the effective height of the compression zone.

$\eta$ : factor defining the effective strength of concrete.

$x$ : distance of the neutral axis from the extreme compression fiber

To calculate the moment capacity  $C_c$ ,  $C_s$  and  $T_s$  are required. In order to determine all these forces depth of the neutral axis,  $x$ , needs to be calculated.

For this, an iterative process is used. The following steps are involved in the iteration:



Ref:  
EN 1992-1-1:2004  
Figure 3.5

[Figure 2.2] Flow chart to calculate depth of Neutral Axis

**Note for design of flanged section**

For a flanged section, we need to specify the shape of the section as “T-section” in the **Section Data** dialog box.

1. Determination of  $\lambda$  &  $\eta$

[Table 2.1] Factor for effective height of compression zone and factor for effective strength of concrete

Condition	$\lambda$	$\eta$
$f_{ck} \leq 50\text{MPa}$	0.8	1.0
$50 < f_{ck} \leq 90\text{MPa}$	$0.8 - (f_{ck} - 50)/400$	$1.0 - (f_{ck} - 50)/200$
$f_{ck} > 90\text{MPa}$	0.7	0.8

2. Initial depth of the neutral axis.

Initial depth is assumed to be  $d/2$ , where  $d$  is the distance between extreme compression fiber and center of tension reinforcement.

3. Calculate force of concrete,  $C_c$

$$C_c = \eta f_{cd} \int_{dA} \lambda x \quad (2.1)$$

4. Calculate force of reinforcement,  $T_s$  and  $C_s$

$$C_s = A_{sc} f_{sc} \quad (2.2)$$

$$T_s = A_{st} f_{st} \quad (2.3)$$

where,

$A_{sc}$ : The cross sectional area of compressive reinforcement.

$f_{sc}$ : The stress at the center of the compressive reinforcement.

$A_{st}$ : The cross sectional area of tensile reinforcement.

$f_{st}$ : The stress at the center of the tensile reinforcement.

In order to calculate the stress of reinforcing steel,  $f_{st}$  or  $f_{sc}$ , the appropriate strain is calculated by the strain compatibility condition as follows:

- a) At the extreme compression fiber of concrete, strain equal to  $\epsilon_{cu}$  is assumed. Then the strain is calculated at the center of reinforcement assuming a linear stress strain distribution as per Figure 2.1.

$$\epsilon_s = \frac{d_t - x}{x} \epsilon_{cu} \quad (2.4)$$

where,

$\epsilon_s$ : The strain at the level of the reinforcement.

$\epsilon_{cu}$ : The ultimate compressive strain in the concrete. ( $\epsilon_{cu} = \epsilon_{cu1}$ )

$x$ : Neutral axis depth.

$d_t$ : Distance of the rebar from extreme compression fiber


[Table 2.2] Ultimate Strain ( $\epsilon_{cu1}$ ) in Concrete

Condition	$\epsilon_{cu1}$
$f_{ck} \leq 50\text{MPa}$	0.0035
$50 < f_{ck} \leq 90\text{MPa}$	$[2.8 + 27\{(98 - f_{cm})/100\}^4]/1000$ , $f_{cm} = f_{ck} + 8\text{MPa}$
$f_{ck} > 90\text{MPa}$	0.0028

EN1992-1-1:2004  
3.1.7(3)

EN1992-1-1:2004  
Table 3.1





**A** - reinforcing steel tension strain limit

**B** - concrete compression strain limit

**C** - concrete pure compression strain limit

[Figure 2.3] Possible strain distributions in the ultimate limit state

EN1992-1-1:2004  
Figure 6.1

b) Calculate the reinforcement stresses corresponding to the calculated reinforcement strains. (from the stress-strain idealizations)

$$f_s = \begin{cases} \varepsilon_s E_s & (\varepsilon_s \leq \varepsilon_{yd}) \\ f_{yd} & (\varepsilon_s > \varepsilon_{yd}) \end{cases} \quad (2.5)$$

The forces of tensile reinforcement and compressive reinforcement are calculated in the above manner.

5. Check if the assumed depth of neutral axis is suitable or not. For this purpose, the convergence criteria is checked. If the following condition is met, then the assumed  $x$  is used as depth of neutral axis:

$$\left| \frac{C-T}{T} \right| < 0.01 \quad (\text{Tolerance})$$

If aforementioned condition is not fulfilled then, new depth of neutral axis is assumed by “Bisection Method (Numerical analysis)”.


If the above criteria is not met after 20 iterations, then:

- We get output “Not converge” in Message window.
- The model needs to be modified as follows:
  - Increase section size.
  - Modify the rebar information (position, numbers, spacing, etc.)

6. Calculate moment resistance  $M_{Rd}$

Once the neutral axis is obtained, moment resistance can be calculated by multiplying the axial forces with eccentricity from the neutral axis.

$$M_{Rd} = C_c a_c + C_s a_{sc} + T_s a_{st} \quad (2.6)$$



[Figure 2.4] Forces and distances from neutral axis depth for  $M_{Rd}$

7. Check moment resistance ratio:

$$\frac{M_{Ed}}{M_{Rd}} \leq 1$$

where,

$M_{Ed}$  : Design bending moment is chosen for the load combinations which are available as per Section 2.1.5.

$M_{Rd}$  : Moment capacity of the section.

Depending on the ratio, the results are displayed in the various forms as mentioned in Section 2.4.

### 2.1.3 Design Criteria for Rebars

To choose the size of the rebars which should be used for the reinforcement, the specifications can be provided in **Design criteria for Rebars** dialog box as shown below.

The transverse reinforcement data can also be specified in this dialog box.

❖ Design > Concrete Design Parameter > Design Criteria for Rebars

The 'Design Criteria for Rebars' dialog box is shown with the following settings:

- For Beam Design:**
  - Main Rebar: P20,P25
  - Stirrups: P10
  - Side Bar: P12
  - Arrangement: 2
  - dT: 55 mm
  - dB: 55 mm
  - Consider Spacing Limit for Main Rebar: ☒
  - Spliced Bars: ☒ None
- For Column Design:**
  - Main Rebar: P25,P32
  - Ties/Spirals: P10
  - Arrangement: Y: 2, Z: 2
  - do: 55 mm
  - Consider Spacing Limit for Main Rebar: ☒
  - Spliced Bars: ☒ None
- For Brace Design:**
  - Main Rebar: P20
  - Ties/Spirals: P10
  - Arrangement: Y: 2, Z: 2
  - do: 0 mm
  - Consider Spacing Limit for Main Rebar: ☒
  - Spliced Bars: ☒ 50%
- For Shear Wall Design:**
  - Vertical Rebar: P13
  - Horizontal Rebar: P13
  - End Rebar From: P10
  - Boundary Element Rebar: P10
  - Boundary Element Rebar Space: 200 mm
  - de: 45 mm
  - dw: 45 mm
  - Input Additional Wall Data... button

[Figure 2.5] Design Criteria for Rebars dialog box

where,

dT represents the distance between center of top rebar and extreme top fiber

dB represents the distance between center of bottom rebar and the extreme bottom fiber

When the value of dT and dB is specified as zero, then the default value is taken as minimum of:

- I.  $\max [H_c/10, B_c/10, 2.5"/63.5 \text{ mm}]$
- II.  $3"/76.2 \text{ mm}$

- ❖ Design > Concrete Design Parameter > Design Criteria for Rebars > Rebar...

KS	JIS	CNS	ASTM	BS/EN	UNI	IS	GB	CSA
<input type="checkbox"/> D6	<input type="checkbox"/> D6	<input type="checkbox"/> D10	<input type="checkbox"/> #3	<input type="checkbox"/> P5	<input type="checkbox"/> P4	<input type="checkbox"/> P6	<input type="checkbox"/> d4	<input type="checkbox"/> 10M
<input type="checkbox"/> D10	<input type="checkbox"/> D10	<input type="checkbox"/> D13	<input type="checkbox"/> #4	<input type="checkbox"/> P6	<input type="checkbox"/> P5	<input type="checkbox"/> P8	<input type="checkbox"/> d5	<input type="checkbox"/> 15M
<input type="checkbox"/> D13	<input type="checkbox"/> D13	<input type="checkbox"/> D16	<input type="checkbox"/> #5	<input type="checkbox"/> P7	<input type="checkbox"/> P6	<input type="checkbox"/> P10	<input type="checkbox"/> d6	<input type="checkbox"/> 20M
<input type="checkbox"/> D16	<input type="checkbox"/> D16	<input type="checkbox"/> D19	<input type="checkbox"/> #6	<input type="checkbox"/> P8	<input type="checkbox"/> P8	<input type="checkbox"/> P12	<input type="checkbox"/> d8	<input type="checkbox"/> 25M
<input type="checkbox"/> D19	<input type="checkbox"/> D19	<input type="checkbox"/> D22	<input type="checkbox"/> #7	<input type="checkbox"/> P9	<input type="checkbox"/> P10	<input type="checkbox"/> P16	<input type="checkbox"/> d10	<input type="checkbox"/> 30M
<input type="checkbox"/> D22	<input type="checkbox"/> D22	<input type="checkbox"/> D25	<input type="checkbox"/> #8	<input type="checkbox"/> P10	<input type="checkbox"/> P12	<input type="checkbox"/> P18	<input type="checkbox"/> d12	<input type="checkbox"/> 35M
<input type="checkbox"/> D25	<input type="checkbox"/> D25	<input type="checkbox"/> D29	<input type="checkbox"/> #9	<input type="checkbox"/> P11	<input type="checkbox"/> P14	<input type="checkbox"/> P20	<input type="checkbox"/> d14	<input type="checkbox"/> 45M
<input type="checkbox"/> D29	<input type="checkbox"/> D29	<input type="checkbox"/> D32	<input type="checkbox"/> #10	<input type="checkbox"/> P12	<input type="checkbox"/> P16	<input type="checkbox"/> P22	<input type="checkbox"/> d16	<input type="checkbox"/> 55M
<input type="checkbox"/> D32	<input type="checkbox"/> D32	<input type="checkbox"/> D36	<input type="checkbox"/> #11	<input type="checkbox"/> P13	<input type="checkbox"/> P18	<input type="checkbox"/> P25	<input type="checkbox"/> d18	
<input type="checkbox"/> D35	<input type="checkbox"/> D35	<input type="checkbox"/> D39	<input type="checkbox"/> #14	<input type="checkbox"/> P16	<input type="checkbox"/> P20	<input type="checkbox"/> P28	<input type="checkbox"/> d20	
<input type="checkbox"/> D38	<input type="checkbox"/> D38	<input type="checkbox"/> D43	<input type="checkbox"/> #18	<input checked="" type="checkbox"/> P20	<input type="checkbox"/> P22	<input type="checkbox"/> P32	<input type="checkbox"/> d22	
<input type="checkbox"/> D41	<input type="checkbox"/> D41	<input type="checkbox"/> D50		<input checked="" type="checkbox"/> P25	<input type="checkbox"/> P24	<input type="checkbox"/> P36	<input type="checkbox"/> d25	
<input type="checkbox"/> D43	<input type="checkbox"/> D51	<input type="checkbox"/> D57		<input type="checkbox"/> P32	<input type="checkbox"/> P26	<input type="checkbox"/> P40	<input type="checkbox"/> d28	
<input type="checkbox"/> D51				<input type="checkbox"/> P40	<input type="checkbox"/> P30		<input type="checkbox"/> d32	
<input type="checkbox"/> D57					<input type="checkbox"/> P32		<input type="checkbox"/> d36	
					<input type="checkbox"/> P36		<input type="checkbox"/> d40	
					<input type="checkbox"/> P40			

[Figure 2.6] Rebar Size dialog box

The following European rebar sizes are available:

P5, P6, P7, P8, P9, P10, P11, P12, P13, P16, P20, P25, P32, P40.

Maximum of 5 Rebar Sizes can be selected.

The data specified above will be applied to all the members of a model. If the user wants to specify different rebar criteria for certain members then that can be specified in **Design Criteria for Rebars by Member** dialog box. For that member, information provided here will override the information defined in **Design Criteria for Rebar** dialog box.

- ❖ Design > Concrete Design Parameter > Design Criteria for Rebar by Member

General | Steel | Concrete | SRC

Design Criteria for Rebars by Member

Beam | Column | Brace | Wall

Option  
☒ Add/Replace ☐ Delete

Main Rebar : P20  
 Stirrups : P10  
 Arrangement : 2  
 Side Bar : P12

dT : 0 mm  
 dB : 0 mm

Select Ductility Class  
☒ DCH (High Ductility)  
☐ DCM (Medium Ductility)

☒ Consider Spacing Limit  
 Spliced Bars :  
☒ None ☐ 50% ☐ 100%

Apply Close

[Figure 2.7] Design Criteria for Rebars by Members dialog box

### 2.1.4 Concrete checking for beams

midas Gen is capable of both design and checking of sections. The difference in design and check can be explained as below:

If the user performs the Concrete Code Design function then based on the section size and the factored load, rebar data such as rebar size and spacing is determined by the program. Therefore, the design can be performed when the section size is defined without rebar data.

If the user needs to perform the strength and serviceability check for the user specified rebar data (rebar diameter, number of rebars and design parameters), then the user can perform the Concrete Code Check function. The rebar data can be specified as mentioned in the section below.

#### 2.1.4.1 Rebar Input for Beam Checking

The rebar data for concrete code checking can be specified in the **Modify Beam Rebar data**. In midas Gen, both top and bottom rebar must be defined to perform concrete code checking.

The data can be entered for layer 1 and layer 2 of the top and the bottom reinforcement.

The values of  $dT$  and  $dB$  need to be specified appropriately.  $dT$  and  $dB$  cannot be specified as zero.

For transverse reinforcement the rebar size, number of legs and spacing of the stirrups can be specified.

❖ *Design > Concrete Design Parameter > Modify Beam Rebar Data*

**Modify Beam Rebar Data**

SECT	Name	Bar
411	G1	In
412	G2	In
413	G3	In
414	G4	In
415	B1	In
421	WG1	In
422	WG2	In

☐ Create Sub Section

Element List : 1to10 70to79 139to148 208to217

**Beam Property**

Diagram showing dimensions:  $H_c$ ,  $B_c$ ,  $dT$ ,  $dB$ .

☐ All Section ☐ Both End & Center ☒ Each End & Center

Rebar		End(I)	Center	End(J)
Main	Top	1 1 P6	1 P20	1 P25
		2 0 P6	0 P20	1 P25
	Bot	2 0 P20	1 P25	0 P20
		1 0 P20	4 P25	1 P20
Stirrup		P10 2 @ 70	2 @ 80	1 @ 70
Skin		0	0	0

Concrete Face to Center of Rebar ( $dT$ ,  $dB$ ): 55 , 55 mm

☐ Detail Figure

Diagram showing rebar layout for End(I), Center, and End(J).

☐ Same Main Rebar Size at Top and Bottom  
☐ Same Main Rebar Size at I, M and J  
☒ Same Main Rebar Size at Each Layer


Add/Replace Delete Close

[Figure 2.8] Modify Beam Rebar Data dialog box

#### 2.1.5 Design load combinations

The load combinations specified as **Strength/Stress** in the **Concrete Design** tab of **Load Combinations** dialog box will be used for concrete design. The program also supports the Auto Generation of the load combinations as per EN 1990:2002. The limitations mentioned in the Section 1.3.6 are applied to the auto generation of the load combinations.

## ❖ Results&gt;Load Combinations



[Figure 2.9] Load Combinations dialog box

## 2.2 Design for flexure with Axial Force

### 2.2.1 Requirements

For limiting the compressive strain in concrete, the following conditions need to be checked:

$$\text{Check for Axial Force } \frac{N_{Ed}}{N_{Rd}} \leq 1$$

$$\text{Check for Biaxial Moment } \frac{M_{Ed}}{M_{Rd}} \leq 1$$

$$\text{Check for Moment about major axis } \frac{M_{Edy}}{M_{Rdy}} \leq 1$$

$$\text{Check for Moment about minor axis } \frac{M_{Edz}}{M_{Rdz}} \leq 1$$

If any of the above ratios is not satisfied then the section is reported to be Not Good.

### 2.2.2 Magnification of Design Moments

When an element is subjected to an axial load combined with a moment, it will deflect. This deflection will increase the moment at any section in the element by an amount equal to the axial force multiplied by the deflection at that point. This extra moment will cause the resistance of the element to be reduced below that calculated ignoring the deflections. In many practical situations, the effect of deflections is so small that it can be ignored. So, the program compares the slenderness ratio of the member with the allowable slenderness limit in order to determine whether the magnification of moment is required or not.

#### 2.2.2.1 Slenderness ratio

The actual slenderness ratio of a member is calculated using:

$$\lambda = l_0 / i \quad (2.7)$$

where,

$l_0$  is the effective length of the member.

$i$  is the radius of gyration.

Effective Length will be calculated as:

$$l_{0,y} = K_y \times L \quad (2.8)$$


where,

EN1992-1-1:2004  
5.8.3.2(1)

$L$  is the unbraced length as specified in Section 1.3.2.

$K_y$  is the effective length factor. The effective length factor can be specified as shown below.

❖ Design > General Design Parameter > Effective Length Factor (K)




The dialog box has tabs for General, Steel, Concrete, and SRC. The 'Effective Length Factor(K)' dropdown is set to 'Effective Length Factor(K)'. Under the 'Option' section, 'Add/Replace' is selected. Under the 'Factor' section, 'Ky' and 'Kz' are both set to 1. 'Apply' and 'Close' buttons are at the bottom.

[Figure 2.10] Effective Length Factor dialog box

Effective Length factor can also be calculated by the program automatically depending on the information provided in **Definition of Frame** dialog box as shown below:

Refer to online help for the explanation of auto calculation.

❖ Design > General Design Parameters > Definition of Frame



The dialog box has a 'Definition of Frame' section with radio buttons for 'Unbraced | Sway' and 'Braced | Non-sway' for both X and Y directions. The 'Design Type' section has radio buttons for '3-D', 'X-Z Plane', 'Y-Z Plane', and 'X-Y Plane'. The 'Auto Calculate Effective Length Factors' checkbox is checked. 'OK' and 'Close' buttons are at the bottom.

[Figure 2.11] Definition of Frame dialog box

### 2.2.2.2 Limiting value of slenderness ratio

$$\lambda_{min} = \frac{A.B.C}{\sqrt{n}} \quad (2.7)$$

where,

$A = 1/(1+0.2\phi_{ef})$ . It can be specified by user. Default value is 0.7 (code recommendation)

$B = \sqrt{1 + 2\omega}$ . It can be specified by user. Default value is 1.1 (code recommendation)

$C = 1.7 - r_m$ .

$r_m = M_{01}/M_{02}$

$M_{01}$  and  $M_{02}$  are end moments of column.  $M_{02}$  is numerically greater of both.  $M_{01}/M_{02} > 0$  for single curvature bending and less than 0 for double curvature bending.

Code recommends that If  $r_m$  is not known,  $C=0.7$  may be used. Constant value of  $C$  can be specified. Also, the program can calculate the factor  $C$  and  $r_m$  based on  $M_{01}$  and  $M_{02}$ .

$n = N_{Ed}/A_c f_{cd}$ . this is the normalized normal force.

EN1992-1-1:2004  
5.8.3.1(1)

❖ Design &gt; Concrete Design Parameter &gt; Concrete Design Code

[Figure 2.12] Concrete Design Code dialog box

### 2.2.2.3 Magnification of Moments

The slenderness ratio,  $\lambda$  (as obtained in 2.2.2.1) is compared to limiting slenderness ratio,  $\lambda_{\min}$ . If P- $\Delta$  Analysis has not been performed and  $\lambda > \lambda_{\min}$ , then the moments are magnified as per the specifications of the code in order to account for the second order moments. If  $\lambda < \lambda_{\min}$  or P- $\Delta$  Analysis has been performed, then the specifications of the code are not used to magnify the design moments.

EN 1992-1-1:2004 specifies the following two methods of moment magnification.

- Based on Nominal Stiffness
- Based on Nominal Curvature

midas Gen uses Nominal Curvature Method.

As per Nominal Curvature Method, the overall design moment,  $M_{Ed}$  is computed as:

$$M_{Ed} = M_{0Ed} + M_2 \quad (2.8)$$

where,

$$M_{0Ed} = 0.6 M_{02} + 0.4 M_{01} \geq 0.4 M_{02}$$

This is valid only if no transverse load exists between supports. In case the transverse load exists between the supports,  $M_{0Ed} = M_{02}$ . In that case, it is recommended to perform P- $\Delta$  Analysis.

$$M_2 = N_{Ed} \times e_2$$

$M_2$  is the additional second order moment.

where,

$$e_2 = (1/r)l_0^2/c$$

$e_2$  is the deflection.

$l_0$  is effective length as specified in Section 2.2.2.1.

$c$  depends on curvature distribution, program uses  $c = 10$  as recommended by code.

The value of  $c$  cannot be changed by user.

$$1/r = K_r K_\phi 1/r_0$$

Curvature

$$K_r = (n_u - n)/(n_u - n_{bal})$$

Correction factor for axial load

$$n = N_{Ed}/A_c f_{cd}$$

Relative axial force.

$$n_u = 1 + \omega$$

$$\omega = 0.105.$$

(Recommended) Different value cannot be specified.

$$n_{bal} = 0.4$$

(Recommended) Different value cannot be specified.

EN1992-1-1:2004  
5.8.8.2(1)

$$K_{\phi} = 1 \quad (\text{Factor for accounting creep})$$

$$1/r_0 = \varepsilon_{yd}/(0.45d)$$

$$\varepsilon_{yd} = f_{yd}/E_s$$

The above calculations are performed for major and minor directions separately.

For the wall the magnification is performed for in-plane bending. If design is also performed for out-of-plane bending, then the above check will also be performed for out-of-plane bending. The choice of design for out-of-plane bending can be specified in **Input Additional Wall Data** dialog box.

### 2.2.3 Determination of the Eccentric Axial Load Capacity

The following procedure is followed to determine the eccentric load capacity of the column:

1. Calculate the eccentricities of bi-axially loaded column:


$$e_{cy} = |M_{Edz}/N_{Ed}|$$

$$e_{cz} = |M_{Edy}/N_{Ed}|$$

$$e = |M_{Ed}/N_{Ed}|$$

$$\text{Angle of axis of bending} = \tan^{-1} |e_{cy}/e_{cz}|$$

Angle of rotation of neutral axis at the ultimate limit state is determined by the program.



[Figure 2.13] Forces and Moments on a member with eccentric axial load

where,

$$M_{Ed} = \sqrt{M_{Edy}^2 + M_{Edz}^2}$$

2. Calculate the axial load capacity for concentric loading

#### Maximum Axial Compression

$$N_{Rd} = (\eta \cdot f_{cd}) \cdot (A_g - A_{st}) + f_{yd} \cdot A_{st} \quad (2.9)$$

where,

$N_{Rd}$  is Axial load (compression) capacity for concentric loading

$\eta$  is the factor for effective strength of concrete

$f_{cd}$  is design strength of concrete as mentioned in Section 2.1.3

$A_g$  is the gross area of column  $A_g = b \cdot h$

$A_{st}$  is the total area of steel in column.

$f_{yd}$  is design yield strength of steel as mentioned in Section 2.1.3

#### Maximum Axial Tension

$$N_{Rdt} = -f_{yd} \cdot A_{st} \quad (2.10)$$

where,

$N_{Rdt}$  is Axial Load (Tension) Capacity for concentric loading

$f_{yd}$  design yield strength of steel

$A_{st}$  is the area of steel

3. Compute capacity of concrete stress block.

#### Height of compression zone

X is the height of the compression zone. For the first trial, the balanced failure is assumed hence  $X = c_b$ .


$$c_b = \frac{\varepsilon_{cu}}{\varepsilon_{cu} + \varepsilon_s} d \quad (2.11)$$

where,

$c_b$  is the depth of neutral axis for section failing in balanced condition

$d$  is the distance of extreme compression fiber from farthest reinforcement





[Figure 2.14] Stress strain distribution in concrete column with eccentric axial load

**Effective height of compression zone**

$$a = \lambda \cdot X \cdot A_{st} \quad (2.12)$$

where,

$\lambda$  is the factor for effective height of compression zone.

$A_{com}$  is the effective area of concrete in compression. It is calculated based on  $a$ .

**Compression Force in Concrete**

$$C_c = \eta \times f_{cd} \times A_{com} \quad A_{st} \quad (2.13)$$

**Moment due to compression force**

$$M_{RdCy} = C_c \cdot D_{Ccz} \quad (2.14)$$

$$M_{RdCz} = C_c \cdot D_{Ccy} \quad (2.15)$$

where,

$D_{Ccy}$  is distance of centroid of compression zone from geometric center of

section along y-axis

$D_{Ccz}$  is distance of centroid of compression zone from geometric center of

section along z-axis

**4. Compute capacity of reinforcement** **$F_{si}$  is force of the  $i^{th}$  reinforcement**

$$F_{si} = A_{si} \cdot f_{si} \quad (2.16)$$

where,

$f_{si}$  is stress in the  $i^{th}$  reinforcement

$$f_s = \begin{cases} \epsilon_s E_s & (\epsilon_s \leq \epsilon_{yd}) \\ f_{yd} & (\epsilon_s > \epsilon_{yd}) \end{cases}$$

where,

$\epsilon_{si}$  is strain in the  $i^{th}$  reinforcement

At the extreme compression fiber of concrete, strain equal to  $\epsilon_{cu}$  is assumed. Then the strain is calculated at the center of reinforcement assuming a linear stress strain distribution as shown in Figure 2.14.

$A_{si}$  is the area of the  $i^{th}$  rebar

**Moment due to force in rebar**

i. About the element local y-axes

$$M_{RdNy} = F_{si} \times d_{zi} \quad (2.17)$$

ii. About the element local z-axes

$$M_{RdNz} = F_{si} \times d_{yi} \quad (2.18)$$

where,

$d_{zi}$  is distance of  $i^{th}$  reinforcement from the geometric center of the section in the element local  $z$ -axis (as shown in Figure 2.14)

$d_{yi}$  is distance of  $i^{th}$  reinforcement from the geometric center of the section in the element local  $y$ -axis (as shown in Figure 2.14)

#### **Cumulative axial force and moment resistance**

Axial force and the moment due to all the rebars are calculated as follows:

$$\begin{aligned} N_s &= \sum (F_{si}) \\ M_{RdNy} &= \sum (M_{RdNy_i}) \\ M_{RdNz} &= \sum (M_{RdNz_i}) \end{aligned}$$

#### 5. Compute capacity ( $N_{Rd}, M_{Rd}$ ) of the section

$$\begin{aligned} N_{Rd} &= C_c + N_s \quad d_{yi} \\ M_{Rdy} &= M_{RdCy} + M_{RdNy} \\ M_{Rdz} &= M_{RdCz} + M_{RdNz} \\ M_{Rd} &= \sqrt{M_{Rdy}^2 + M_{Rdz}^2} \end{aligned} \quad (2.19)$$

#### 6. Compare the eccentricity with the actual eccentricity

##### **Eccentricity**

$$e_c = M_{Rd}/N_{Rd}$$

##### **Actual eccentricity**

$$e = M_{Ed}/N_{Ed}$$

If  $e_c = e$ , then  $X$  is the height of the compression zone. For the first trial  $e_c = e_b$  (balanced eccentricity).


Otherwise new depth is assumed.

Then new value of  $X$  is assumed as follow:

$e < e_b$ , then section is compression controlled and larger value of  $x$  is assumed.


$e > e_b$ , then section is tension controlled and smaller value of  $x$  is assumed.

##### **Case 1: $e < e_b$**



##### **Compression Failure**

##### **Case 2: $e > e_b$**




##### **Tension Failure**


[Figure 2.15] Comparison of Tension Controlled and Compression Controlled Column

#### 7. Check P-M Curve

**The P-M curve is generated for a fixed angle of rotation of neutral axis.**



**3D PM Curve is generated by changing the angle of rotation of neutral axis as follows:**



The output is given in the form of 2-D P-M Interaction Curve as well as 3-D P-M-M Interaction Curve.

### Check the ratio

The following ratios are checked to verify the capacity of the axially loaded member (wall/column):

$$\frac{N_{Ed}}{N_{Rd}} \leq 1$$

$$\frac{M_{Ed}}{M_{Rd}} \leq 1$$

$$\frac{M_{Edy}}{M_{Rdy}} \leq 1$$

$$\frac{M_{Edz}}{M_{Rdz}} \leq 1$$

where,

$M_{Ed}$  : Design bending moment is chosen for the load combinations which are available as per 2.1.5.

$M_{Rd}$  : Moment Capacity of the section.

Depending on the ratio, the results are displayed in various formats box as mentioned in Section 2.4.

### 2.2.4 Design Criteria for Rebars


To choose the size of the rebars that should be used for providing the reinforcement, the specifications can be provided in **Design criteria for rebars** dialog box as shown in Section 2.1.3.

The stirrup data can also be specified in this dialog box.

Data can be specified for both wall and column design.

For wall design the End rebar design method and the spacing of the end rebar can be specified in **Input Additional Wall Data** dialog box as shown below:

❖ *Design > Concrete Design Parameter > Modify Column Rebar Data*



[Figure 2.18] Input Additional Wall Data dialog box


### 2.2.5 Concrete checking for columns & walls

Concrete Code Checking can be performed for column members & wall members as well. The rebar data can be specified for axially loaded members and Ultimate Limit State and Serviceability Limit State can be verified based on that rebar data.

#### 2.2.5.1 Rebar Input for Column Checking

The rebar data for the column can be specified in **Modify Column Rebar Data** dialog box as shown below.

## ❖ Design &gt; Concrete Design Parameter &gt; Modify Column Rebar Data



The dialog box 'Modify Column Rebar Data' contains the following elements:

- Table:**

SECT	Name	Bar
106	C1	In
156	C1A	In
206	C2	In
306	C3	-
406	C4	-
- Buttons:** 'Create Sub Section' (disabled), 'Element List' (text: '45to390by69 48to393by69 49to39').
- Diagram:** A square cross-section of a column with dimensions  $B_c$  (width) and  $H_c$  (height). It shows the center of rebar ( $do$ ) and the concrete face to center of rebar ( $do$ ). The coordinate system  $(y, z)$  is centered at the origin.
- Rebar Data Table:**


Rebar		Data	
Main	Numbers	4	P25
	Rows	2	P25
	Corner	<input type="checkbox"/>	P25
Ties/ Spirals	End(I & J)	y	2
		z	2
	Center(M)	y	2
		z	2
		y	2
		z	2
- Concrete Face to Center of Rebar( $do$ ):** 63.5 mm
- Type of Hoop Rebar:** ☒ Ties ☐ Spirals
- Detail Figure:** Two diagrams showing the rebar layout for 'End(I & J)' and 'Center(M)' with coordinate systems  $(y, z)$ .
- Buttons:** 'Add/Replace', 'Delete', 'Close'.

[Figure 2.19] Modify Column Rebar Data dialog box

**2.2.5.2 Rebar Input for Wall Checking**

The rebar data for the wall can be specified in **Modify Wall Rebar Data** dialog box as shown below.

## ❖ Design &gt; Concrete Design Parameter &gt; Modify Wall Rebar Data



The dialog box 'Modify Wall Rebar Data' contains the following elements:

- Table:**

Wall ID	Wall Mark	Start Story	End Story	Bar
1	W1	1F	Roof	-
2	W2	1F	Roof	-
3	W2	1F	Roof	-
4	W2	1F	Roof	-
5	W1	1F	Roof	-
6	W2	1F	Roof	-
7	W2	1F	Roof	-
8	W1	1F	Roof	-
- Buttons:** 'Create Sub Wall ID' (disabled).
- Story:** 1F ~ Roof
- Rebar Data Table:**

Rebar	Data
Vertical	P13 @ 0
Horizontal	P13 @ 0
End 2	P10 @ 0
BE Horizontal	P10 @ 200
- Diagram:** A cross-section of a wall showing vertical rebar with dimensions  $dw$  (concrete face to center of rebar),  $de$  (effective depth), and  $vDist$  (vertical distance between rebar).
- Concrete Face to Center of Rebar( $dw, de$ ):** 0.0508, 0.0508 m
- Use Model Thickness:** ☒ 0.000 m
- Buttons:** 'Add/Replace', 'Delete', 'Close'.

[Figure 2.20] Modify Wall Rebar Data dialog box

**2.2.6 Design load combinations**

The specifications in Section 2.1.5 are applied.

## 2.3 Design for Shear

### 2.3.1 Requirements


Shear resistance of the section ( $V_{Rd}$ ) should be greater than the design shear force for the section ( $V_{Ed}$ ).

To satisfy Limit state of Shear Resistance the following condition should be met:

$$V_{Ed} \leq V_{Rd}$$

### 2.3.2 Calculation of Shear Resistance ( $V_{Rd}$ )

If  $V_{Ed}$  is smaller than the shear resistance of concrete, then shear reinforcement is not required and shear resistance is calculated by concrete only. If design shear force exceeds shear resistance calculated from concrete then the shear resistance is calculated by shear reinforcement only.



[Figure 2.21] Flow chart to calculate  $V_{Rd}$

#### 2.3.2.1 Members not requiring design shear reinforcement

In member for which  $V_{Ed} \leq V_{Rd,c}$ , no shear reinforcement is required. In those members the program provides the minimum specified shear reinforcement as per Section 4.1.2 and 4.2.2.

For such sections, the shear resistance

$$V_{Rd} = V_{Rd,c} \quad d_{yi} \quad (2.20)$$

For calculating the design shear resistance of concrete, larger of the following two values is adopted:

$$V_{Rd,c} = [C_{Rd,c} k (100 \rho_l f_{ck})^{1/3} + k_1 \sigma_{cp}] b_w d \quad (2.21)$$

$$V_{Rd,c} = [0.035 k^{3/2} f_{ck}^{1/2} + k_1 \sigma_{cp}] b_w d \quad (2.22)$$

where,

$$C_{Rd,c} = 0.18/\gamma_c$$

$$k = 1 + \sqrt{200/d} \leq 2.0$$

$$\rho_l = A_{sl}/(b_w d) \leq 0.02$$

$\sigma_{cp} = N_{Ed}/A_c$ , In beam design,  $\sigma_{cp}$  is applied as zero since axial force is not considered.

$$k_1 = 0.15$$

$A_{sl}$  is the area of the tensile reinforcement, which extends  $\geq (l_{bd} + d)$  beyond the section considered. For beam section, program considers  $A_{sl}$  as the area of the tensile reinforcement provided. For column sections, the  $A_{sl}$  is used as the  $A_{st}/2$  i.e half of the area of the longitudinal reinforcement.

#### 2.3.2.2 Members requiring design shear reinforcement

For the members for which the design shear force exceeds the shear resistance provided by concrete, the shear resistance is calculated as the resistance provided by shear reinforcement.

$$V_{Rd} = V_{Rd,s} + V_{ccd} + V_{td} \quad d \quad (2.23)$$


where,

$V_{ccd}$ : shear component of the force in the compression area, in the case of inclined compression chord.

$V_{td}$ : shear component of the force in the tensile reinforcement, in the case of inclined tensile chord.

EN1992-1-1:2004  
6.2.2(1)

EN1992-1-1:2004  
6.2.1(2)




[Figure 2.22] Shear component for members with inclined chords

Since, inclined chord is not considered therefore the shear resistance is calculated using shear reinforcement only.

$$V_{Rd} = V_{Rd,s} \quad (2.24)$$

Design of shear reinforcement is based on truss model as specified in Section 6.2.3 of EN 1992-1-1:2004




[Figure 2.23] Truss model and notation for shear reinforced members

$\theta$  is the angle between the concrete compression strut and the beam axis perpendicular to the shear force.  $\alpha$  is the angle between shear reinforcement and the beam axis perpendicular to the shear force. The program provides the shear reinforcement perpendicular to the beam axis. So,  $\alpha = 90^\circ$ . Any other value of  $\alpha$  cannot be specified by the user.

$\theta$  can be specified by user in **Concrete Design Code** dialog box as explained below:

❖ Design > Concrete Design Parameters > Design Code ...



[Figure 2.24] Concrete Code Design dialog box

Shear resistance of members with shear reinforcement can be calculated depending on the type of shear reinforcement as specified in the table below.

[Table 2.3]  $V_{Rd,s}$  and  $V_{Rd,max}$ ,  $A_{sw,max}$ 

Parameter	Formula	Remarks
$V_{Rd,s}$	$\frac{A_{sw} (0.9 d) f_{ywd}}{s} \cot \theta$	$A_{sw}$ is cross-sectional area of the shear reinforcement. $s$ is the spacing of stirrups.
$V_{Rd,max}$	$\frac{f_{cd} (0.9 d b)}{\cot \theta + \tan \theta} \alpha_{cw} v_1$	$f_{ywd}$ is design yield strength of the shear reinforcement. $v_1$ is Strength reduction factor for concrete cracked in shear.
$A_{sw,max}$	$\frac{0.5 \alpha_{cw} v_1 f_{cd} b s}{f_{ywd}}$	$\alpha_{cw}$ is Coefficient taking account of the state of the stress in the compression chord. $\alpha_{cw}$ is always applied as 1.0 in beam design.

EN1992-1-1:2004  
6.2.3(4)

EN1992-1-1:2004  
6.2.3(3)

Using,  $V_{Rd,s} = V_{Ed}$ , spacings of the shear reinforcement is calculated.

$V_{Rd,max}$  is the design value of the maximum shear force which can be sustained by the member, limited by crushing of the compression struts.

$A_{sw}/s$  is calculated and compared with  $A_{sw,max}/s$ .

[Table 2.4(a)] Strength reduction factor for concrete cracked in shear,  $v_1$

National Annex	$f_{ywd} \geq 0.8f_{ywk}$	$f_{ywd} < 0.8f_{ywk}$	
		$f_{ck} < 60\text{MPa}$	$f_{ck} \geq 60\text{MPa}$
<b>Recommended</b>	$0.6 \left(1 - \frac{f_{ck}}{250}\right)$	0.6	$0.9 - \frac{f_{ck}}{200} > 0.5$
<b>Singapore</b>	$0.6 \left(1 - \frac{f_{ck}}{250}\right)$	$0.54(1 - 0.5 \cos \alpha) = 0.54$	$(0.84 - f_{ck}/200)(1 - 0.5 \cos \alpha) \geq 0.5$ $= (0.84 - f_{ck}/200) \geq 0.5$

[Table 2.4(b)] Strength reduction factor for concrete cracked in shear,  $v_1$

National Annex	$f_{ywd} \geq 0.8f_{ywk}$		$f_{ywd} < 0.8f_{ywk}$	
	$f_{ck} \leq 70\text{MPa}$	$f_{ck} > 70\text{MPa}$	$f_{ck} < 60\text{MPa}$	$f_{ck} \geq 60\text{MPa}$
<b>Italy</b>	0.5	$0.7 \left(1 - \frac{f_{ck}}{250}\right)$	0.7	$\frac{0.9 - \frac{f_{ck}}{200}}{0.85} > 0.5$

[Table 2.5] Recommended values of Coefficient  $\alpha_{cw}$


Condition	$\alpha_{cw}$
$0 < \sigma_{cp} \leq 0.25f_{cd}$	$1 + \sigma_{cp}/f_{cd}$
$0.25f_{cd} < \sigma_{cp} \leq 0.5f_{cd}$	1.25
$0.5f_{cd} < \sigma_{cp} \leq 1.0f_{cd}$	$2.5(1 - \sigma_{cp}/f_{cd})$

$\sigma_{cp}$ : The mean compressive stress, measured positive, in the concrete due to the design axial force. In beam design,  $\sigma_{cp}$  is applied as zero since axial force is not considered.

### 2.3.3 Design Criteria for Rebars

Size of the rebar to be used for providing the shear reinforcement can be specified in **Design Criteria for Rebars** dialog box. The number of legs to be used for shear reinforcement can also be specified.

❖ Design > Concrete Design Parameter > Design Criteria for Rebar...



[Figure 2.25] Design Criteria for Rebars dialog box



### 2.3.4 Shear in Concrete Code Checking

When Beam Checking or Column checking is performed, then checks for shear are also applied. The data for the transverse reinforcement can be specified in the program. The data can be specified in **Modify Beam Rebar Data**, **Modify Column Rebar Data** and **Modify Wall Rebar Data** dialog box. Refer to section 2.1.4.1, 2.2.5.1 and 2.2.5.2 for the usage of these dialog boxes. The program allows the user to specify rebar size, rebar spacing and the number of legs for stirrup.

For beams the data can be specified for i-end, j-end and the middle section.

For columns the same data can be specified for the two ends of the member and different data can be specified for center of the column.

### 2.3.5 Design Load Combinations

The specifications of section 2.1.5 are applied.

In case the shear reinforcement is required, the governing Load combination for shear design is not decided on the basis of the magnitude of the shear force. The governing load combination is decided on the basis of the ratio of the shear force and shear capacity.

Now, if there are two shear forces  $V_{Ed1}$  and  $V_{Ed2}$  such that  $V_{Ed1} > V_{Ed2}$ .  $V_{Rd,s}$  (Shear Strength provided by steel) and  $V_{Rd,c}$  (Shear Strength provided by concrete) will be calculated. If  $V_{Ed1}/V_{Rd,s}$  is less than the  $V_{Ed2}/V_{Rd,c}$ , then  $V_{Ed2}$  will be governing load combination for shear design, even if  $V_{Ed2}$  is smaller of the two shear forces.


## 2.4 Verification of Design/Check Results

midas Gen provides the results of design/check in various formats. The following design outputs are available.

### 2.4.1 Design Result Dialog Box

The design results can be checked in **Beam Design Result Dialog/Column Design Result Dialog/Wall Design Result Dialog** box as shown below.

❖ *Design > Concrete Code Design > Beam Design...*




[Figure 2.26] Beam Design Result dialog box

Similarly, the design results can be checked for column and walls. The dialog box for design results of column members can be accessed from **Design > Concrete Code Design > Column Design**. The dialog box for design results of wall can be accessed from **Design > Concrete Code Design > Wall Design**.


### 2.4.2 Design/Check Reports

The program provides the results in the following kind of report formats:

- i. Graphic Report
- ii. Detail Report
- iii. Summary Report



[Figure 2.27] Graphic Report for Beam Design



[Figure 2.28] Detailed Report for Beam Design

MIDAS/Text Editor - [Untitled.rcs]

File Edit View Window Help

00187  
00188 \*.MEMB = 10, SECT = 411 (G1, RECT), Span = 10.2000  
00189 \*.Bc = 0.4500, Hc = 0.7000  
00190 \*.fck = 30000.0, fyk = 500000, fyw = 400000  
00191  
00192 POS CHK | N-M\_Ed( LCB) AsTop Rebar | P-M\_Ed( LCB) AsBot Rebar | V\_Ed( LCB) Asw Stirrups  
00193  
00194 I OK | 375.841( 2) 0.0049 10-P25 | 47.4562( 3) 0.0009 3-P20 | 187.713( 2) 0.0022 2-P10 Ø70  
00195 M OK | 0.00000( 13) 0.0006 2-P20 | 310.828( 2) 0.0034 7-P25 | 134.243( 2) 0.0020 2-P10 Ø80  
00196 J OK | 346.586( 2) 0.0049 10-P25 | 63.1686( 7) 0.0009 3-P20 | 182.375( 2) 0.0022 2-P10 Ø70  
00197  
00198  
00199  
00200 \*.MEMB = 11, SECT = 412 (G2, RECT), Span = 7.20000  
00201 \*.Bc = 0.4000, Hc = 0.7000  
00202 \*.fck = 30000.0, fyk = 500000, fyw = 400000  
00203  
00204 POS CHK | N-M\_Ed( LCB) AsTop Rebar | P-M\_Ed( LCB) AsBot Rebar | V\_Ed( LCB) Asw Stirrups  
00205  
00206 I OK | 183.388( 9) 0.0015 3-P25 | 22.2076( 11) 0.0006 2-P20 | 99.0871( 7) 0.0009 2-P10 Ø180  
00207 M OK | 39.3944( 11) 0.0006 2-P20 | 43.9243( 2) 0.0006 2-P20 | 68.0898( 3) 0.0006 2-P10 Ø260  
00208 J OK | 185.128( 5) 0.0015 3-P25 | 21.6764( 13) 0.0006 2-P20 | 99.6170( 3) 0.0009 2-P10 Ø180  
00209  
00210  
00211  
00212 \*.MEMB = 12, SECT = 412 (G2, RECT), Span = 7.20000  
00213 \*.Bc = 0.4000, Hc = 0.7000  
00214 \*.fck = 30000.0, fyk = 500000, fyw = 400000  
00215  
00216 POS CHK | N-M\_Ed( LCB) AsTop Rebar | P-M\_Ed( LCB) AsBot Rebar | V\_Ed( LCB) Asw Stirrups  
00217  
00218 I OK | 297.775( 7) 0.0015 3-P25 | 1.09638( 11) 0.0006 2-P20 | 156.981( 7) 0.0009 2-P10 Ø180  
00219 M OK | 49.6797( 5) 0.0006 2-P20 | 64.3412( 6) 0.0006 2-P20 | 95.4280( 8) 0.0006 2-P10 Ø260  
00220 J OK | 298.241( 3) 0.0015 3-P25 | 0.96975( 13) 0.0006 2-P20 | 157.110( 3) 0.0009 2-P10 Ø180  
00221  
00222  
00223  
00224 midas Gen - RC-Beam Design [ Eurocode2:04 ] Gen 2014  
00225  
00226  
00227  
00228  
Ready  
Ln 0 / 3527, Col 1 NUM

[Figure 2.29] Summary Report for Beam Design

# Serviceability Limit State

The serviceability limit state is verified only when we perform Concrete Code Check. It is not verified when Concrete Code Design is performed.

## 3.1 Serviceability Type Load Combination

The load combinations specified as **Serviceability** in the **Concrete Design** Tab of **Load Combinations** dialog box will be used for serviceability limit state check. The program supports the auto generation of the load combinations as per EN 1990:2002.

### 3.1.1 Definition of Short Term and Long Term Load


For the purpose of crack control, the **Load Cases** need to be specified as either short term load or long term load.

Depending on the type of the load case, the program classifies the load cases automatically. Information regarding the classification of load cases can be viewed/modified in **Short/Long term Load Case** dialog box as shown below.

[Table 3.1] Classification of load based on duration

Type of load	Description
<b>Long term</b>	If the load case is any of the following types, it is classified as long term: D: Dead Load L: Live Load. LR: Roof Live Load. IL: Live Load Impact
<b>Short term</b>	If the type of load case is other than specified above, then it will be classified as short term load case

❖ *Design > General Design Parameter > Short/Long term Load Case*



[Figure 3.1] Short/Long term Load Case dialog box

If a load combination consists of any of the short term load case then the load combination will be classified as short term type. Otherwise it will be classified as long term type.


### 3.1.2 Classification of Serviceability type Load Combinations

EN 1990:2002 classifies the serviceability type load combinations in following three types:

- i. Quasi-Permanent
- ii. Frequent
- iii. Characteristic

The load combinations that are auto generated are automatically classified in the above types. The information regarding the classification of the load combinations can be viewed/modified in **Serviceability Load Combination Type** dialog box as shown below.

❖ *Design > General Design Parameter > Serviceability Load Combination Type*




[Figure 3.2] Serviceability Load Combination Type dialog box

## 3.2 Serviceability Parameters

Various parameters should be specified for performing the serviceability limit state check. The default parameters are known to the program. Depending on the national annex selected in Concrete Design Code dialog box, the parameters are automatically updated. The parameters can be viewed/modified in the program.

❖ *Design > General Design Parameter > Serviceability Parameters*



[Figure 3.3] Serviceability Parameters dialog box

### 3.3 Stress Limitation

The compressive stress in concrete should be limited to avoid:

- formation of micro-cracks which might reduce durability
- excessive creep

The program applies the stress checks for both situations. The first step in applying the stress check is to determine whether the section is cracked or uncracked for the applicable load cases. The section is uncracked if the following criteria is fulfilled:

$$\sigma_c (\text{tension}) \leq \sigma_{ca} (\text{tension})$$

where,

$$\sigma_c (\text{tension}) = M_u Z_{bar} / I_{yy}, \text{ stress in extreme tension fiber}$$

$M_u$  is the bending moment for a load combination.

$Z_{bar}$  is the distance of Neutral Axis from extreme tension fiber.

$I_{yy}$  is the moment of inertia.

$I_{yy}$  and  $Z_{bar}$  are calculated assuming elastic behavior of concrete in an uncracked transformed section.

$$\sigma_{ca} (\text{tension}) = \max [f_{ctm}, (1.6-h/1000)f_{ctm}] \quad (3.1)$$

[Table 3.2] Mean Value of Axial Tensile Strength,  $f_{ctm}$

Condition	$f_{ctm}$
$\leq \text{C50/60}$	$0.30 f_{ck}^{2/3}$
$> \text{C50/60}$	$2.12 \ln(1+(f_{cm}/10))$

For column members  $\sigma_c$  (tension) is calculated considering the axial load and the biaxial bending:

$$\Sigma_c (\text{tension}) = P_u / A_c + (M_{uy} Z_{bar}) / I_{yy} + (M_{uz} Y_{bar}) / I_{zz} \quad (3.2)$$

If  $\sigma_c (\text{tension}) \geq \sigma_{ca} (\text{tension})$ , then the section is cracked. For cracked sections, the program updates the section properties for stress check.

#### 3.3.1 Stress Verification to avoid micro cracking

EN 1992-1-1:2004 specifies "Longitudinal cracks may occur if the stress level under the characteristic combination of loads exceeds a critical value. In the absence of other measures it may be appropriate to limit the compressive stress to a value  $k_1 f_{ck}$  in areas exposed to environments of exposure classes XD, XF and XS" and "Unacceptable cracking or deformation may be assumed to be avoided if, under the characteristic combination of loads, the tensile stress in the reinforcement does not exceed  $k_3 f_{yk}$ ". Therefore, to fulfill these two specification, program applies the stress check for both reinforcement as well as concrete.

The stress verification is performed for characteristic type of serviceability load combinations. After determining that whether the section is cracked or not, the appropriate method is applied as explained below:

##### 3.3.1.1 Un-cracked Sections

In order to satisfy the stress check for concrete, the following criteria should be met:

$$\sigma_c (\text{Comp.}) \leq \sigma_{ca} (\text{Comp.})$$

The stress is calculated at the extreme compression fiber of the section.

$$\sigma_c (\text{Comp.}) = M_u * (H - Z_{bar}) / I_{yy} \quad (3.3)$$

where,

$M_u$  is the bending moment for a load combination.

$(H - Z_{bar})$  is the distance of Neutral Axis from extreme compression fiber.

$I_{yy}$  is the moment of inertia.

$I_{yy}$  and  $Z_{bar}$  are calculated assuming elastic behavior of concrete in an uncracked transformed section.

For column members  $\sigma_c$  (Comp) is calculated considering the axial load and the biaxial bending:

EN1992-1-1:2004  
3.1.8(1)

EN1992-1-1:2004  
Table 3.1

EN1992-1-1:2004  
7.2(2)

EN1992-1-1:2004  
7.2(5)

$$\sigma_c (\text{Comp.}) = P_u/A_c + M_{uy} (H-Z_{bar}) / I_{yy} + M_{uz} (B-Y_{bar}) / I_{zz} \quad (3.4)$$

where,

$H$  is the whole depth of cross-section along  $z$ -axis.

$B$  is the whole width of cross-section along  $y$ -axis.

The limiting value of the stress in concrete is calculated as:

$$\sigma_{ca} (\text{Comp.}) = k_1 f_{ck} \quad (3.5)$$

$k_1$  can be specified in Serviceability Parameters. The following values are automatically adopted:

[Table 3.3] Coefficient  $k_1 \sim k_4$

	$k_1$	$k_2$	$k_3$	$k_4$
<b>Recommended</b>	0.6	0.45	0.8	1.0
<b>Italy</b>	0.6	0.45	0.8	0.9
<b>Singapore</b>	0.6	0.45	0.8	1.0

The parameter  $k_4$  is not used by the program.

In order to satisfy the stress check for reinforcement, the following criteria should be met:

$$\sigma_s \leq \sigma_{sa}$$

Stress in reinforcement is calculated as below:

$$\sigma_s = M_u * (d - z_{bar}) * n / I_{yy} \quad (3.6)$$

$n$  is the Long term ratio of modulus of Elasticity.

The limiting value of the stress in the reinforcement is calculated as:

$$\sigma_{sa} = k_3 f_{yk} \quad (3.7)$$

$k_3$  can be specified in Serviceability Parameters as defined in Section 3.2.

For column members, the check is applied only for concrete. The stress in reinforcement is not checked.

### 3.3.1.2 Cracked Sections

The stresses are calculated for various load cases using the suitable modular ratio and then they are added to get the stresses due to the particular load combination.

The following components are used:

1. Dead Load Cases

$$\sigma_{c,D} = M_{u,D} * z_{bar} / I_{yy}$$

$$\sigma_{s,D} = M_{u,D} * (d - z_{bar}) * n / I_{cr} \quad (\text{Long term ratio is used})$$

2. Live Load Cases

$$\sigma_{c,L} = M_{u,L} * z_{bar} / I_{yy}$$

$$\sigma_{s,L} = M_{u,L} * (d - z_{bar}) * n / I_{cr} \quad (\text{Long term ratio is used})$$

3. Other Load Cases

$$\sigma_{c,E} = M_{u,E} * z_{bar} / I_{yy}$$

$$\sigma_{s,E} = M_{u,E} * (d - z_{bar}) * n / I_{cr} \quad (\text{Short term ratio is used})$$

where,

$M_{u,D}$  is the bending moment for a load combination.

$(z_{bar})$  is the distance of Neutral Axis from extreme compression fiber.

$I_{cr}$  is the moment of inertia.

$I_{cr}$  and  $z_{bar}$  are calculated assuming elastic behavior of concrete in a cracked transformed section. The neutral axis is located by equating moment of areas. Then the  $I_{cr}$  is calculated about the neutral axis.

Then the stress in concrete are calculated as:

$$\sigma_c = \sigma_{c,D} + \sigma_{c,L} + \sigma_{c,E}$$

$$\sigma_s = \sigma_{s,D} + \sigma_{s,L} + \sigma_{s,E}$$

For concrete,  $\sigma_c \leq k_1 \times f_{ck}$

For steel,  $\sigma_s \leq k_3 \times f_{yk}$

If a column members is cracked, then this procedure is not carried out for it.



### 3.3.2 Check for linear Creep

EN 1992-1-1:2004 specifies "If the stress in the concrete under the quasi-permanent loads is less than  $k_2 f_{ck}$ , linear creep may be assumed. If the stress in concrete exceeds  $k_2 f_{ck}$ , non-linear creep should be considered." After determining whether the section is cracked or not under quasi-permanent load combinations, the appropriate method is applied as explained below:

#### 3.3.2.1 Uncracked Sections

Method specified in 3.3.1.1 is used to calculate the compressive stress and the allowable compressive stress.

Quasi-Permanent type of combinations are used.

The allowable stress is calculated as  $\sigma_{ca}(\text{comp.}) = k_2 \times f_{ck}$ .

If  $\sigma_c(\text{comp.}) \leq \sigma_{ca}(\text{comp.})$  and  $\sigma_s(\text{comp.}) \leq \sigma_{sa}(\text{comp.})$  then linear creep may be assumed.

#### 3.3.2.2 Cracked sections

Method specified in 3.3.1.1 is used to calculate the compressive stress and the allowable compressive stress.

Quasi-Permanent Type of combinations are used.

The allowable stress is calculated as  $\sigma_{ca}(\text{comp.}) = k_2 \times f_{ck}$ .

If  $\sigma_c(\text{comp.}) \leq \sigma_{ca}(\text{comp.})$  and  $\sigma_s(\text{comp.}) \leq \sigma_{sa}(\text{comp.})$  then linear creep may be assumed.

If the column member are cracked, then this procedure is not carried out for them.

## 3.4 Crack width

For beam sections, cracking shall be limited to satisfy the following condition.

Crack width,  $w_k \leq$  Crack width limit,  $w_{\max}$

Crack width is only calculated if the stress in concrete at the extreme tension fiber exceeds the allowable tension stress.

### 3.4.1 Calculate crack widths

The crack width is calculated using the following formula:

$$w_k = S_{f,\max} (\epsilon_{sm} - \epsilon_{cm}) \quad (3.8)$$

#### 1. Determine $\epsilon_{sm} - \epsilon_{cm}$

$$\epsilon_{sm} - \epsilon_{cm} = \frac{\sigma_s - k_t \frac{f_{ct,eff}}{\rho_{p,eff}} (1 + \alpha_e \rho_{p,eff})}{E_s} \geq 0.6 \frac{\sigma_s}{E_s} \quad (3.9)$$

where,

$\epsilon_{sm}$  The mean strain in the reinforcement under the relevant combination of loads, including the effect of imposed deformations and taking into account the effects of tensile stiffening.

$\epsilon_{cm}$  The mean strain in the concrete between cracks.

$\sigma_s$  The stress in the tension reinforcement.

$\alpha_e E_s / E_{cm}$ .

$k_t$  A factor dependent on duration of the load.

[Table 3.4] Factor  $k_t$

Condition	$k_t$
Short term loading	0.6
Long term loading	0.4

$$\rho_{p,eff} = \frac{A_s + \xi_1^2 A_p'}{A_{c,eff}} = \frac{A_s}{A_{c,eff}} \quad (3.10)$$


EN1992-1-1:2004  
7.3.4(1)

EN1992-1-1:2004  
7.3.4(2)

$A_p'$ : The area of pre or post-tensioned. Since the tendon is not considered in program,  $A_p' = 0$ .

$A_{c,eff}$ : The effective area of concrete in tension,  $b_w \times h_{c,eff}$ .

$$h_{e,eff} = \min \left[ 2.5(h - d), \frac{h - x}{3}, \frac{h}{2} \right] \quad (3.11)$$



[Figure 3.5] Calculation of Effective tension area

## 2. Determine $s_{r,max}$

The maximum crack spacing,  $s_{r,max}$  is calculated as shown in the table below.

$$s_{r,max} = k_3 c + \frac{k_1 k_2 k_4 \phi}{\rho_{p,eff}} \quad (3.12)$$

EN1992-1-1:2004  
7.3.4(2)

where,

$\phi$  is bar diameter. In case different sizes are used,  $\phi_{eq}$  should be calculated as:

$$\phi_{eq} = \frac{n_1 \phi_1^2 + n_2 \phi_2^2}{n_1 \phi_1 + n_2 \phi_2}$$

The program uses the  $\phi$  of the outer layer.

$c$  is cover to the longitudinal reinforcement.

$k_1$ : A coefficient accounting the bond properties of rebar (0.8 for high bond bars)

$k_2$ : Coefficient accounting for distribution of strain. (0.5 for bending)

$k_3$ : 3.4 (recommended values)

$k_4$ : 0.425 (recommended values)

These values can't be changed.

### 3.4.2 Limiting Crack Width, $w_{max}$

For reinforced members without prestressing tendon, limiting values of crack width,  $w_{max}$ , are given in the table below.

[Table 3.5] Limiting Crack Width,  $w_{max}$

Exposure Class	Serviceability Load combination Type		
	Quasi-Permanent	Frequent	Characteristic
X0	0.4	User defined	Not Checked
XC1			
XC2	0.3		
XC3			
XC4			
XD1	0.3		
XD2			
XD3			
XS1	0.3		
XS2			
XS3			
XF1*	Not Checked		0.2
XF2*			
XF3*			
XF4*			
XA1*			
XA2*			
XA3*			

### 3.4.2.1 Exposure Class

Exposure class can be specified in Serviceability Parameters as mentioned in Section 3.2.

## 3.5 Deflection Check

EN 1992-1-1:2004 specifies to apply deflection check for certain sections that do not meet the depth/span ratio criteria. But midas Gen calculates the deflection for all the members and compares the deflection with the allowable value irrespective of the span/depth ratio.

There is no deflection check for the complete structure. Deflection check is applied for each member separately.


Deflection verification is performed by comparing the relative deflection of the member to deflection limit. Deflection is verified for Quasi-permanent and Characteristic load combinations. The limit value is specified by the user in **Serviceability Parameter** dialog box.

## 3.6 Verification of Results

The checking results can be checked in various formats in midas Gen.

### 3.6.1 Check Result dialog box

The checking results can be checked in **Beam Checking Result Dialog** box as shown below.




[Figure 3.6] Beam Checking Result dialog box

Similarly, the checking results can be checked for column sections and walls. The dialog box for checking results of column members can be accessed from **Design > Concrete Code Check > Column Checking**. The dialog box for checking results of walls can be accessed from **Design > Concrete Code Check > Wall Checking**.


### 3.6.2 Design/Check Reports

The program provides the results in the following kind of report formats:


- Graphic Report
- Detail Report
- Summary Report



[Figure 3.7] Graphic Report for Beam Checking



[Figure 3.8] Detail Report for Beam Checking



[Figure 3.9] Summary Report for Beam Checking

# Detailing of Members

When the program provides the reinforcement to the section, then checks are applied for minimum and maximum allowable area of steel. Minimum areas of reinforcement are given in order to prevent a brittle failure, wide cracks and also to resist forces arising from restrained actions. Along with that the program also applies the checks for the spacing of the rebars. There should be sufficient space between the resulting bars of members to allow access for vibrators and good compaction of the concrete. The details of these checks are discussed in this section.

## 4.1 Detailing rules for Beam Design

### 4.1.1 Longitudinal Reinforcement

The following specifications of EN1992-1-1:2004 are considered by the program while providing the reinforcement.

Maximum area of longitudinal reinforcement is calculated as:

$$A_{s,max} = 0.04 A_c \quad (4.1)$$

EN1992-1-1:2004  
9.2.1.1 (3)

Minimum area of longitudinal reinforcement is calculated as:

$$A_{s,min} = 0.26 \frac{f_{ctm}}{f_{yk}} b_t d \geq 0.0013 b_t d \quad (4.2)$$

EN1992-1-1:2004  
9.2.1.1(1)

where,

$b_t$  denotes the mean width of the tension zone. For rectangular sections,  $b_t$  is equal to section width. For a T-beam width of web is used by the program.

$f_{ctm}$  is taken as specified in 3.1.

For providing the adequate spacing in the bars, the program takes care of the following code specifications:

The clear distance (horizontal and vertical) between individual parallel bars or horizontal layers of parallel bars should be not less than the maximum of:

- $k_1 \cdot \text{bar diameter}$
- $(d_g + k_2 \text{ mm})$  where  $d_g$  is the maximum size of aggregate.
- 20 mm

The recommended values of  $k_1$  and  $k_2$  are used which are specified as 1 and 5 mm respectively.

### 4.1.2 Shear Reinforcement

Minimum required shear reinforcement is calculated by the program as below:

$$\rho_{w,min} = 0.08 \sqrt{f_{ck}} / f_{yk} \quad (4.3)$$

EN1992-1-1:2004  
9.2.2(5)

where,

$\rho_w$  is the shear reinforcement ratio

The maximum longitudinal spacing between shear assemblies is taken as the minimum of:

$$s_{l,max} = 0.75d (1 + \cot \alpha) = 0.75d \text{ (for } \alpha=90^\circ) \quad (4.4)$$

$$s = A_{sw} / (b_w \cdot \rho_{w,min}) \quad (4.5)$$

EN1992-1-1:2004  
9.2.2(6)

where,

$A_{sw}$  is the area of shear reinforcement within length  $s$

$s$  is the spacing of the shear reinforcement

$b_w$  is the breadth of the web of the member

$\alpha$  is the angle between shear reinforcement and the longitudinal axis. It is applied

as  $90^\circ$  in midas Gen.

To consider constructability, the program rounds off the required spacing to the lower 10 mm value.

## 4.2 Detailing Rules for column design

### 4.2.1 Longitudinal Reinforcement

EN 1992-1-1:2004 specifies that longitudinal bars should have a diameter of not less than  $\varphi_{\min}$ .

Varying values of  $\varphi_{\min}$  are specified in National Annexes.

This needs to be taken care by the user. When specifying the design criteria for rebars in **Design > Concrete Design Parameter > Design Criteria for Rebars**, the bars bigger than  $\varphi_{\min}$  in diameter should be chosen by the user.

EN1992-1-1:2004  
9.5.2(1)

The minimum allowed amount of longitudinal reinforcement for a column is specified as greater of the two values.

- i.  $A_{s,\min} = 0.10 N_{Ed}/f_{yd}$
- ii.  $0.002 A_c$


EN1992-1-1:2004  
9.5.2(2)

The maximum value of amount of longitudinal reinforcement is specified as  $A_{s,\max}$ . The recommended value of  $A_{s,\max}$  is  $0.04 A_c$ .

EN1992-1-1:2004  
9.5.2(3)

The value of  $A_{s,\max}$  can be viewed/modified in **Limiting Maximum Rebar Ratio** dialog box as shown below:

❖ *Design > Concrete Design Parameters > Limiting Maximum Rebar Ratio*



[Figure 4.1] Limiting Maximum Rebar Ratio dialog box

### 4.2.2 Shear Reinforcement

For column members, the diameter of the transverse reinforcement should not be less than, greater of the two below:

- i. 6 mm
- ii.  $\frac{1}{4}$  times the maximum diameter of the longitudinal bars

EN1992-1-1:2004  
9.5.3(1)

This needs to be taken care by the user. When specifying the design criteria for rebars in **Design > Concrete Design Parameter > Design Criteria for Rebars**, the suitable bar diameter should be chosen.

In case the shear reinforcement is not required, the minimum reinforcement is provided as:

$$\rho_{w,\min} = 0.08 \sqrt{f_{ck}} / f_{yk} \quad (4.6)$$

$$s = A_{sw} / \rho_w \cdot b_w \cdot \sin \alpha \quad (4.7)$$

The  $s$  is calculated and used for maximum spacing.

The spacing of the transverse reinforcement along the column should not exceed  $s_{cl,tmax}$ :

The recommended value is the least of the following three distances:

- i. 20 times the minimum diameter of the longitudinal bars
- ii. Lesser dimension of the column
- iii. 400 mm

This specification is taken care by the program itself.

To consider constructability, the program rounds off the required spacing to the lower 10 mm value.

## 4.3 Detailing Rules for Wall design

### 4.3.1 Vertical Reinforcement

The maximum amount of the vertical reinforcement should be applied as:

$$A_{s,v,max} = 0.04 A_c \quad (4.8)$$

The ratio can be viewed/edited in Limiting Maximum Rebar Ratio dialog box as shown in previous section.

The minimum amount of vertical reinforcement should be applied as:

$$A_{s,v,min} = 0.002 A_c \quad (4.9)$$

This is the recommended value and it cannot be edited by the user.

### 4.3.2 Horizontal Reinforcement

The minimum horizontal reinforcement is provided as per the following specifications:

$$\rho_{w,min} = \max [0.25 A_{s,y} / A_c, 0.001] \quad (4.10)$$

The maximum spacing of the horizontal reinforcement shall be limited to minimum of the following:

- I.  $2 * A_{s,v} / (\rho_{w,min} h_w)$
- II. 400 mm

For wall design, the detailing rules for shear reinforcement are same as that of column design.

EN1992-1-1:2004  
9.6.2(1)


EN1992-1-1:2004  
9.6.3(1)

EN1992-1-1:2004  
9.6.3(2)



# RC Design Tutorial

Eurocode2 Design Guide for midas Gen





midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*


## Eurocode Design of a Multi-story RC Building

- Part I – EC2 in Gen
- Part II – Model & Design Parameters
- Part III – ULS Member Design
- Part IV – ULS Member Checks
- Part V – SLS Member Checks

1
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*

### Eurocode Design of Reinforced Concrete Building as per EN 1992-1-1: 2004



**Overview**

- Eurocode Design of Reinforced Concrete Building
- Model
  - 6-story Reinforced Concrete Building
  - Element: Wall, Beam
- Load & Boundary Condition
  - Self Weight
  - Floor Loads
  - Wind Loads
  - Seismic Loads
  - Supports
- Analysis
  - Linear Static Analysis

2
MIDAS Information Technology Co., Ltd.

### Reinforced Concrete Design Features in midas Gen

- Gen provides automatic design for beam, column and shear wall.
- Section checking with the given data.
- Ultimate limit state and Serviceability limit state design and/or checking.
- Default load combinations as per Eurocode 2.
- Static wind loads as per Eurocode 1-4: 2005
- Static seismic loads and response spectrum function as per Eurocode 8-1: 2004
- Capacity design as per Eurocode 8-1 can be applied by checking on “Apply EC8:04 Capacity Design” option in Concrete Design Code dialog box.
- Available Section shapes
  - ✓ Column: Rectangle, Circular, Hollow circular
  - ✓ Wall: Rectangle
  - ✓ Beam: Rectangle, T-shape

#### Note:

Torsion should be checked by the user.

For meshed slab and wall design, we can use Meshed Slab/Wall Design function.

### Ultimate Limit State (ULS) Design

#### (1) Bending without axial force

▪ Assuming  $K$  and  $K'$  have been determined:

where:

$$K = M / bd^2 f_{ck}$$

$$K' = 0.598\delta - 0.18\delta^2 - 0.21$$

where:

$$\delta \leq 1.0 = \text{Moment Redistribution Ratio (Factor)}$$

▪ If  $K \leq K'$  (singly reinforced)

$$A_{s1} = M / f_{yd} z$$

where:

$A_{s1}$  is area of compression steel (in layer 1).

$$f_{yd} = f_{yk} / \gamma_s$$

$$z = d[0.5 + 0.5(1 - 3.53K)^{0.5}] \leq 0.95d$$

■ If  $K > K'$  (Doubly Reinforced)

$$A_{s2} = (M - M') / f_{sc} (d - d_2)$$

where:

$A_{s2}$  is area of compression steel (in layer 2).

$$M' = K' b d^2 f_{ck}$$

$$f_{sc} = 700 (x_u - d_2) / x_u$$

$$f_{sc} = f_{yd}$$

where:

$d_2$  is effective depth to compression steel.

$$x_u = (\delta - 0.4) d$$

$$A_{s1} = M' / f_{yd} z + A_{s2} f_{sc} / f_{yd}$$

For Minimum and Maximum Required Rebar Area

$$A_{s,min} = 0.26 (f_{ctm} / f_{yk}) b_i d \geq 0.0013 b_i d$$

## (2) Bending with axial force

### Slenderness Ratio

Second order effects may be ignored if the slenderness  $\lambda$  is below a certain value  $\lambda_{lim}$ .

$$\lambda = l_0 / i$$

$$\lambda_{lim} = 20 \cdot A \cdot B \cdot C / \sqrt{n}$$

### Design Bending moment

$$M_{Ed} = \max[M_{0Ed} + M_2, M_{02}, M_{01} + 0.5M_2]$$

■ where:

$M_{Ed}$  is design moment.



$M_{0Ed}$  is equivalent first order moment including the effect of imperfection (at about mid height) and may be taken as  $M_{0e}$

where:

$$M_{0e} = (0.6M_{02} + 0.4M_{01}) \geq 0.4M_{02}$$

$M_{02}, M_{01}$  is first order end moments at ULS including allowances for imperfections.  $|M_{02}| \geq |M_{01}|$


$M_2 = N_{Ed} e_2$ ; nominal second order moment in slender column



- For symmetrically reinforced members, the loads and moments at the points ④~⑪ may be calculated by the formula below.

$$P_u = \eta f_{cd} \lambda x b + A'_s f'_s - A_s f_s$$

$$M_u = \eta f_{cd} \lambda x b \left( \frac{h}{2} - 0.5 \lambda x \right) + A'_s f'_s \left( \frac{h}{2} - d' \right) + A_s f_s \left( d - \frac{h}{2} \right)$$



- A** - reinforcing steel tension strain limit
- B** - concrete compression strain limit
- C** - concrete pure compression strain limit

### (3) Shear

- Shear resistance of a member with shear reinforcement is equal to:

$$V_{Rd} = V_{Rd,s}$$

- In regions of the member where  $V_{Ed} \leq V_{Rd,c}$  no calculated shear reinforcement is necessary.
- In regions where  $V_{Ed} > V_{Rd,c}$  sufficient shear reinforcement should be provided in order that  $V_{Ed} \leq V_{Rd}$ .

#### Members not requiring design shear reinforcement

$$V_{Rd,c} = [C_{Rd,c} k (100 \rho_1 f_{ck})^{1/3} + k_1 \sigma_{cp}] b_w d$$

With a minimum of

$$V_{Rd,c} = (v_{min} + k_1 \sigma_{cp}) b_w d$$

#### Members requiring design shear reinforcement

The shear resistance,  $V_{Rd}$  is the smaller value of:

$$V_{Rd,s} = (A_{sw} / s) z f_{yw} \cot \theta$$

and

$$V_{Rd,max} = \alpha_{cw} b_w z v_1 f_{cd} / (\cot \theta + \tan \theta)$$



### Serviceability Limit States (SLS) Design

#### (1) Stress Limitation

▪The compressive stress shall be limited to a value  $k_1 f_{ck}$  in order to avoid **longitudinal cracks under the characteristic combination of loads**. A value of  $K_1$  can be defined by the user and default value is '0.6'.

▪If the stress in the concrete under the **quasi-permanent loads** is less than  $k_2 f_{ck}$ , linear creep may be assumed. If the **stress in concrete exceeds  $k_2 f_{ck}$ , non-linear creep should be considered**. A value of  $K_2$  can be defined by the user and default value is '0.45'.

▪**Unacceptable cracking or deformation** may be assumed to be avoided if, **under the characteristic combination of loads**, the tensile stress in the reinforcement does not exceed  $k_3 f_{yk}$ . A value of  $K_3$  can be defined by the user and default value is '0.8'.

▪Where the stress is caused by an imposed deformation, the tensile stress should not exceed  $k_4 f_{yk}$ . A value of  $K_4$  can be defined by the user and default value is '1.0'.

#### (2) Crack Control

▪A limiting calculated crack width,  $w_{max}$ , taking into account the proposed function and nature of the structure and the costs of limiting cracking, should be established.

Exposure Class	Reinforced members and prestress members with unbounded tendons	Prestressed members with bonded tendons
	Quasi-permanent load combination	Frequent load combination
X0,XC1	0.3 (Default value)	0.2
XC2,XC3,XC4 XD1,XD2,XS1,XS2,XS3	0.4	0.2
		Decompression

#### (3) Deflection Control

▪The appearance and general utility of the structure could be impaired when the calculated sag of a beam, slab or cantilever subjected to quasi-permanent loads exceeds  $\text{span}/250$ .

▪For the deflection subjected to characteristic loads can be checked by user defined limit. Default limit is  $\text{Span}/250$ .

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

**Beam detailing**

The following data are required to be input for Beam design:

- **Beam section size (b, h)**
- **Cover to rebar center** *default* =  $\min\{\max(h/10, 63.5\text{mm}), 76.2\text{mm}\}$
- **Bar size**
  - ✓ **Main rebar:** Up to 5 sizes simultaneously selected, which GEN will use to find the most appropriate.
  - ✓ **Stirrup/Link:** One size can be selected.
  - ✓ **P5, P6, P7, P8, P9, P10, P11, P12, P13, P16, P20, P25, P32, and P40 are available.**
- **Arrangement (= Number of legs of the transverse or shear reinforcement)**
  - ✓ **Only one case can be selected among the numbers from 2 to 20.**

13
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

**Beam detailing**

The following conditions are applied to Beam design:

- **Maximum rebar ratio of main rebar, EN 1992-1-1 9.2.1.1**

$$A_{s,\max} = 0.04A_c$$
- **Minimum rebar ratio of main rebar, EN 1992-1-1 9.2.1.1**

$$A_{s,\min} = \max(0.26f_{ctm}/f_{yk}b_id, 0.0013b_id)$$
- **Minimum spacing (= clear distance) of bars, EN 1992-1-1 8.2**

$$= \max(D_{bar}, d_g + 5\text{mm}, 20\text{mm})$$
- **Maximum stirrup spacing, EN 1992-1-1 9.2.2**

$$S_{\max} = \min\{A_{sw}/(b_w\rho_{w,\min}), 0.75d(1 + \cot\alpha)\} \quad \rho_{w,\min} = 0.08\sqrt{f_{ck}}/f_{yk}$$

14
MIDAS Information Technology Co., Ltd.

### Beam detailing

The following are the Design results provided by Gen:

#### Main rebar

- Required rebar area satisfying minimum bar spacing
- Number of bars at top and bottom satisfying minimum bar spacing
- Capacity ratio at I-end, middle, and J-end of beam member
- Up to two layers of rebar can be designed

#### Stirrups/Links


- Required rebar area per unit length
- Spacing of stirrups
- Capacity ratio at I-end, middle, and J-end of beam member
- Check for crushing of compression struts

### Column detailing

The following data are required to be input for Column design:

- Column section size (b, h)
- Cover to rebar center  $default = \min\{\max(h/10, 63.5mm), 76.2mm\}$
- Bar size
  - ✓ Main rebar: Up to 5 sizes simultaneously selected, among which GEN will find the most appropriate.
  - ✓ Tie/Spiral: One size can be selected.
  - ✓ P5, P6, P7, P8, P9, P10, P11, P12, P13, P16, P20, P25, P32, and P40 are available.
- Arrangement (= Number of legs of the transverse reinforcement)
  - ✓ Different number of legs can be applied in the y and z direction.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building


 **Column detailing**

The following conditions are applied to Column design:

- **Maximum rebar ratio of main rebar, EN 1992-1-1 9.5.2**  
 $A_{s,max} = 0.03 A_c$ , which can be modified.
- **Minimum rebar ratio of main rebar, EN 1992-1-1 9.5.2**  
 $A_{s,min} = \max(0.10 N_{ED} / f_{yd}, 0.002 A_c)$
- **Minimum spacing (clear distance) of bars, EN 1992-1-1 8.2**  
 $= \max(D_{bar}, d_g + 5mm, 20mm)$
- **Maximum stirrup spacing, EN 1992-1-1 9.5.3 & 9.2.2**  
 $S_{cl,t max} = \min\{20 D_{bar}, b, h, 400mm, A_{sw} / (b_w \rho_{w,min})\}$      $\rho_{w,min} = 0.08 \sqrt{f_{ck}} / f_{yk}$   
*The maximum spacing is reduced by a factor 0.6 at the i and j-end of the column.*

17
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

 **Column detailing**

The following are the design results provided by Gen:

**Main rebar**

- Number of bars satisfying minimum bar spacing
- Capacity ratio for the most critical part among I-end, middle, and J-end of column member
- Biaxial P-M interaction diagram

Note. Two layers of rebar or bundle bars are not applicable.

**Stirrup/Links**

- Required rebar area per unit length
- Spacing of ties/spirals
- Capacity ratio for the most critical part of column member (I-end, middle, and J-end)
- Check for crushing of compression struts

18
MIDAS Information Technology Co., Ltd.

### Shear Wall detailing

The following data are required to be input for Shear Wall design:


- Wall section size (L, h)
- Cover to rebar center *default = 50.8mm*
- Bar size
  - ✓ Vertical rebar: Up to 5 sizes simultaneously selected, among which GEN will find the most appropriate.
  - ✓ End rebar: One size can be selected, then program will find the most appropriate, greater than or equal to the one selected.
  - ✓ Horizontal rebar: One size can be selected.
  - ✓ P5, P6, P7, P8, P9, P10, P11, P12, P13, P16, P20, P25, P32, and P40 are available.
- Spacing of vertical rebar
  - ✓ Select as many spacings as you want program to try
- Spacing of horizontal rebar
- Design method

### Shear Wall detailing

The following conditions are applied to Shear Wall design:

- Maximum rebar ratio of vertical rebar, EN 1992-1-1 9.6.2  
 $A_{s,max} = 0.04 A_c$ , which can be modified.
- Minimum rebar ratio of vertical rebar, EN 1992-1-1 9.6.2  
 $A_{s,min} = 0.002 A_c$
- Maximum spacing of horizontal rebars, EN 1992-1-1 9.6.3  
 $S_{max} = \min \{ 2 A_{s,v} / (\rho_{v,min} h), 400mm \}$      $\rho_{v,min} = \max (0.25 A_{s,v} / A_c, 0.001)$

midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*

 **Shear Wall detailing**

Followings are the design results provided by Gen:

**Vertical rebar**

- Spacing of vertical rebar
- Capacity ratio for the most critical part among top and bottom of wall
- Uniaxial P-M interaction diagram

**Horizontal**

- Required rebar area per unit length
- Spacing of horizontal rebar
- Capacity ratio for the most critical part among top and bottom of wall
- Check for crushing of compression struts

21
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*

**PART II - Contents**



[The Model File](#)

[Performing the Analysis](#)

[Design Parameters](#)


[ULS Design](#)

22
MIDAS Information Technology Co., Ltd.



midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*

### Opening the Pre-generated Model File



1. File > Open Project...
2. Select "EC2 Design".
3. Click [Open] button.

⚠ This tutorial is intended to illustrate design procedure as per Eurocode2. Therefore, the geometry creation, boundary assignment, load application will be skipped. For the aforementioned, refer to "Seismic Design for RC Building" tutorial.

⚠ In this tutorial, slab is not included in the model and considered as a rigid diaphragm.

### Analysis

1. Analysis > Perform Analysis

25
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
*Eurocode Design of Multi-story RC Building*

### Parameters for ULS Design

- Load Combinations
- Design Code
- Sway Frame Definitions
- Member Assignment
- Live Load Reduction Factor Modifications
- Unbraced Lengths (L, L<sub>b</sub>)
- Partial Safety Factors
- Concrete and Rebar Properties

26
MIDAS Information Technology Co., Ltd.

• • • 13



midas Gen Tutorial

**Eurocode Design of Multi-story RC Building**

### Load Combinations

1. Results > Combinations...
2. Click on "Concrete Design" tab.
3. Click [Auto Generation...] button.
4. Option: Add
5. Code Selection: Concrete
6. Design Code: Eurocode2:04
7. Click [OK] Button.
8. Click [Close] Button.

**The program automatically creates design load combinations which can be also modified or deleted by the user.**

The 'Automatic Generation of Load Combi...' dialog box is shown with the following settings:

- Option: Add
- Code Selection: Concrete
- Design Code: Eurocode2:04
- Scale Up of Response Spectrum Load Cases: Scale Up Factor: 1.0
- Manipulation of Construction Stage Load Case: ST: Static Load Case, CS: Construction Stage Load Case, ST Only, CS Only, ST+CS
- Consider Orthogonal Effect: Set Load Cases for Orthogonal Effect...
- Factors for variable actions: Live Load: 0.7, Wind Load: 0.6, Snow Load: 0.7
- Partial factors for actions: Gamma.G: 1.4, Gamma.Q: 1.5
- Will Execute Construction Stage Analysis: Consider Losses for Prestress Load Cases: Transfer Stage: 0.9, Service Load Stage: 0.8

The 'Load Combinations' table is as follows:

No	Name	Active	Type	Description
1	CLCB1	Strength/Stress	Add	1.4D + 1.5(1.0LL)
2	CLCB2	Strength/Stress	Add	1.4D + 1.5(1.0LL) +
3	CLCB3	Strength/Stress	Add	1.4D + 1.5(1.0LL) +
4	CLCB4	Strength/Stress	Add	1.4D + 1.5(0.7LL) +
5	CLCB5	Strength/Stress	Add	1.4D + 1.5(0.7LL) +
6	CLCB6	Strength/Stress	Add	1.4D + 1.5(1.0LL) -
7	CLCB7	Strength/Stress	Add	1.4D + 1.5(1.0LL) -
8	CLCB8	Strength/Stress	Add	1.4D + 1.5(0.7LL) -
9	CLCB9	Strength/Stress	Add	1.4D + 1.5(0.7LL) -
10	CLCB10	Strength/Stress	Add	1.0D + 1.0(0.3L) +
11	CLCB11	Strength/Stress	Add	1.0D + 1.0(0.3L) +
12	CLCB12	Strength/Stress	Add	1.0D + 1.0(0.3L) -
13	CLCB13	Strength/Stress	Add	1.0D + 1.0(0.3L) -
14	CLCB14	Semiconsistency	Add	SERV 1.0D + 1.0LL
15	CLCB15	Semiconsistency	Add	SERV 1.0D + 1.0LL
16	CLCB16	Semiconsistency	Add	SERV 1.0D + 1.0LL
17	CLCB17	Semiconsistency	Add	SERV 1.0D + 1.0LL
18	CLCB18	Semiconsistency	Add	SERV 1.0D + 1.0LL
19	CLCB19	Semiconsistency	Add	SERV 1.0D + 1.0LL
20	CLCB20	Semiconsistency	Add	SERV 1.0D + 1.0LL
21	CLCB21	Semiconsistency	Add	SERV 1.0D + 1.0LL

27

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial

**Eurocode Design of Multi-story RC Building**

### Design Code

1. Design > Concrete Design Parameter > Design Code...
2. Design Code: Eurocode2:04
3. Click [OK] button.

### Sway Frame Definitions

1. Design > General Design Parameter > Definition of Frame...
2. X-Direction of Frame: Braced | Non-sway
3. Y-Direction of Frame: Braced | Non-sway
4. Design Type: 3-D
5. Check off "Auto Calculate Effective Length Factors".
6. Click [OK] button.

**In the non-sway frame, applying 1 for the effective length factor will give conservative results.**

The 'Concrete Design Code' dialog box is shown with the following settings:

- Design Code: Eurocode2:04
- National Annex: Italy
- Apply ECB:04 Capacity Design: [ ]
- Strut Angle for Shear Resistance: 45 Deg
- Slenderness Limit: Lambda\_lim = 20\*A\*B\*C/sqrt(n)
- A: 0.7, B: 1.1, C: 1
- Calculate by Program: [ ]
- Moment Redistribution Factor for Beam: 0

The 'Definition of Frame' dialog box is shown with the following settings:

- Definition of Frame: X-Direction of Frame: Braced | Non-sway, Y-Direction of Frame: Braced | Non-sway
- Design Type: 3-D
- Auto Calculate Effective Length Factors: [ ]

28

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Member Assignment

1. Design > General Design Parameter > Member Assignment...

2. Assign Type: Automatic

3. Selection Type: All

4. Click [Apply] button.

5. Click [Close] button.

A single Member can be assigned when the member is consisted of a number of beam elements.

29
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Live Load Reduction Factors (1)

1. Design > General Design Parameter > Modify Live Load Reduction Factor...

2. Option: Add/Replace

3. Reduction Factor: 0.82

4. Applied Components: All Forces

5. View > Select > Identity...

6. Select Type: Story

7. Select "1F"

8. Click [Add] button.

9. Click [Close] button.

10. Click [Apply] button.

**1. Reduction factor for 1st floor columns and walls.**

$$\alpha_n = \frac{2 + (n - 2)\psi_0}{n} = 0.82$$

$n = 5 \quad \psi_0 = 0.7$

EN 1991-1-1 6.3.1.2 (11)

30
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Live Load Reduction Factors (2)

1. Design > General Design Parameter > Modify Live Load Reduction Factor...
2. Option: Add/Replace
3. Reduction Factor: 0.85
4. Applied Components: All Forces
5. View > Select > Identity...
6. Select Type: Story
7. Select "2F".
8. Click [Add] button.
9. Select "Floor".
10. Click [Delete] button.
11. Click [Close] button.
12. Click [Apply] button.

1. Reduction factor for 2nd floor columns and walls.

$$\alpha_n = \frac{2 + (n-2)\psi_0}{n} = 0.85$$

$n = 4 \quad \psi_0 = 0.7$

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Live Load Reduction Factors (3)

1. Design > General Design Parameter > Modify Live Load Reduction Factor...
2. Option: Add/Replace
3. Reduction Factor: 0.9
4. Applied Components: All Forces
5. View > Select > Identity...
6. Select Type: Story
7. Select "3F".
8. Click [Add] button.
9. Select "Floor".
10. Click [Delete] button.
11. Click [Close] button.
12. Click [Apply] button.

1. Reduction factor for 3rd floor columns and walls.

$$\alpha_n = \frac{2 + (n-2)\psi_0}{n} = 0.9$$

$n = 3 \quad \psi_0 = 0.7$

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Unbraced Lengths (L, Lb)

1. Design > General Design Parameter > Unbraced Length(L, Lb)...
2. Option: Add/Replace
3. Unbraced Length – Ly: 0 mm
4. Lz: 0 mm
5. Laterally Unbraced Length: Check on “Do not consider”.
6. View > Select > Select All
7. Click [Apply] button.

⚠ 1. If “0” is entered for Ly and Lz, unbraced lengths will be calculated by the program based on the nodal coordinates of the beam elements.

33
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Partial Safety Factors

**Partial Safety Factors for Material Properties**

Design Code : Eurocode2:04, Italy 2 Update By Code

Partial Safety Factors for Material Properties

Concrete (Gamma_c)	
- Fundamental	1.5
- Accidental (except Earthquakes)	1.2
Steel (Gamma_s)	
- Fundamental	1.15
- Accidental (except Earthquakes)	1
Partial Safety Factors for Material Properties	
Alpha_cc	0.85

3 OK
Close

1. Design > Concrete Design Parameter > Partial Safety Factors for Material Properties...
2. Click [Update By Code] button.
3. Click [OK] button.

34
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete and Rebar Properties

1. Design > Concrete Design Parameter > Modify Concrete Materials...
2. Select "C30/37" from Material List.
3. Rebar Selection – Code: EN04(RC)
4. Grade of Main Rebar: Class B
5. Grade of Sub-Rebar: Class A
6. Click [Modify] button.
7. Click [Close] button.

35
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Design Criteria for Rebar (1)

1. Tools > Preferences...
2. Click on "Design".
3. Concrete – Design Code: Eurocode2:04
4. Rebar – Material Code: EN04(RC)
5. Click [OK] button.

36
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Design Criteria for Rebar (2) – Beam Design

**6. Design > Concrete Design Parameter > Design Criteria for Rebar...**

**7. For Beam Design – Main Rebar: click [Rebar...] button.**

**8. Select P20 and P25.**

**9. Click [OK] button.**

**10. Stirrups: P10, Side Bar: P12**

**11. Arrangement: 2**

**12. dT: 55 mm, dB: 55 mm**

**13. Option of Spliced Bars: None**

37

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Design Criteria for Rebar (3) – Column Design

**14. For Column Design – Main Rebar: click [Rebar...] button.**

**15. Select P25 and P32.**

**16. Click [OK] button.**

**17. Ties/Spirals: P10**

**18. Arrangement: X: 2, Z: 2**

**19. do: 55mm**

**20. Option of Spliced Bars: None**

38

MIDAS Information Technology Co., Ltd.



midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Design Criteria for Rebar (4) –Wall Design

21. For Shear Wall Design – Vertical Rebar: click [Rebar...] button.

22. Select P13 and Click [OK] button.

23. Horizontal Rebar: P13, End Rebar From: P10

24.  $d_v$ : 45 mm,  $d_w$ : 45 mm

25. Click [Input Additional Wall Data...] button.

26. End Rebar Design Method: Method-1

27. Click [OK] button.

28. Click [OK] button.

39
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### ULS Design

**Concrete Beam Design**

**Section for Design**

**Concrete Column Design**

**Concrete Wall Design**

**¶ 1. The “Section for Design” function provides Member design of concrete sections based on the section data defined by the user. It allows you to find the appropriate section without re-analysis.**

40
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete Beam Design (1)

1. Design > Concrete Code Design > Beam Design...
2. Sorted by: Member
3. Click to expand the dialog box.
4. SEL: select MEMB "1".

41
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete Beam Design (2)

5. Click [Graphic...] button.

42
MIDAS Information Technology Co., Ltd.




## midas Gen Tutorial

## Eurocode Design of Multi-story RC Building

### Concrete Beam Design (3)

6. Click **[Detail...]** button.




## midas Gen Tutorial

## Eurocode Design of Multi-story RC Building

### Concrete Beam Design (4)

7. Click [Summary...] button.



45 MIDAS Information Technology Co., Ltd.

46 MIDAS Information Technology Co., Ltd.

midas Gen Tutorial Eurocode Design of Multi-story RC Building

### Section for Design (3)

9. SEL: select SECT "413".  
10. Click [Re-calculation] button.

1. Check results of Section 413 G1 change to OK.

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial Eurocode Design of Multi-story RC Building

### Concrete Column Design (1)

1. Design > Concrete Code Design > Column Design...  
2. Sorted by: Member  
3. Click [ >> ] to expand the dialog box.  
4. SEL: select MEMB "41".

1. As with Beam we may check [Graphic...], [Detail...] & [Summary...] results.

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete Column Design (2)

5. Click [Draw PM Curve...] button.

6. Click [Close] button.

**M-N Interaction Curve Dialog**

Unit : kN , m

Member No. : 41

Section Type : RT

Hc = 0.7000

Bc = 0.6000

4- 2-P25

PM Curve Result :

N Rdmax = 7960.31

N Ed = 2216.61

N Rd = 6095.99

Rat-N = 0.3636

M Ed = 176.034

M Rd = 472.550

Rat-M = 0.3725

Rat-My = 0.3726

Rat-Mz = 0.3725

Eccentricity : m

M Ed/N Ed = 0.07942

Rotation : Deg.

M Edz/M Edy = 52.477

Print Result

Close

49

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete Wall Design (1)

1. Design > Concrete Code Design > Wall Design...

2. Sorted by: Wall ID + story

3. Click [ >> ] to expand the dialog box.

4. SEL: select WID "1" Story "1F".

**Eurocode 2:04 RC-Wall Design Result Dialog**

Code : Eurocode2:04 (Method 1) Unit : N , mm

Primary Sorting Option : WID Story

Sorted by : WID Story

WID	SEL	Wall Mark	Lw	HTw	hw	fw	Ratio	N <sub>Ed</sub>	M <sub>Ed</sub>	V <sub>Ed</sub>	As <sub>V</sub>	V-Rebar	End-Rebar
Story							Rat-V	LCB	LCB	Asw-H	H-Rebar	Bar Layer	
1	1F	W1	3000.0	5000.0	200.00	400.000	0.328	3056223	8.8E+09	1637382	884.67	P13 @300	Not Use
1F		W2	3000.0	5000.0	200.00	400.000	0.992	455469	3.5E+08	662891	884.67	P13 @290	Double
2	1F	W1	3000.0	5000.0	200.00	400.000	0.516	853790	1.7E+09	408535	884.67	P13 @300	Not Use
2F		W2	3000.0	5000.0	200.00	400.000	0.820	1093453	2.2E+09	696204	884.67	P13 @290	Double
3	1F	W1	3000.0	5000.0	200.00	400.000	0.594	488576	2.8E+08	544651	884.67	P13 @300	Not Use
3F		W2	3000.0	5000.0	200.00	400.000	0.983	1704443	3.1E+09	505209	884.67	P13 @300	Not Use
4	1F	W1	3000.0	5000.0	200.00	400.000	0.231	906323	1.3E+09	66350	884.67	P13 @400	Double
4F		W2	3000.0	5000.0	200.00	400.000	0.633	1093453	2.2E+09	696204	884.67	P13 @290	Double
5	1F	W1	3000.0	5000.0	200.00	400.000	0.976	906323	2.2E+09	696204	884.67	P13 @300	Not Use
5F		W2	3000.0	5000.0	200.00	400.000	0.775	1093453	2.2E+09	696204	884.67	P13 @290	Double
6	1F	W1	3000.0	5000.0	200.00	400.000	0.219	3178859	6.5E+09	890729	884.67	P13 @300	Not Use
6F		W2	3000.0	5000.0	200.00	400.000	0.745	1093453	2.2E+09	696204	884.67	P13 @290	Double
7	1F	W1	3000.0	5000.0	200.00	400.000	0.242	2584406	7.0E+09	1644633	884.67	P13 @300	Not Use
7F		W2	3000.0	5000.0	200.00	400.000	0.987	1093453	2.2E+09	696204	884.67	P13 @290	Double
8	1F	W1	3000.0	5000.0	200.00	400.000	0.485	884406	1.7E+09	678041	884.67	P13 @300	Not Use
8F		W2	3000.0	5000.0	200.00	400.000	0.986	1093453	2.2E+09	696204	884.67	P13 @290	Double

Connect Model View

Select A : Unselect All

Graphic... Detail... Summary... <<

Draw PM Curve... Update Rebar Close Copy Table

Result View Option : All OK NG

1. As with Beam we may check [Detail...] & [Summary...] results.

2. As with Column we may Draw PM Curve.

50

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Concrete Wall Design (2)

5. Click [Graphic...] button.

The screenshot displays the midas Gen software interface for concrete wall design. It includes several panels: '1. Design Condition' with material and geometric data; '2. Applied Loads' showing load combinations; '3. Axial Forces and Moments Capacity Check' with various strength ratios; '4. M-N Interaction Diagram' showing two graphs for Major and Minor axes; and '5. Shear Force Capacity Check' with shear strength and ratio calculations.

51
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Manually Entering Rebar and ULS Checking

Enter Rebar Data using “Design > Concrete Design Parameter > Modify Beam/Column/Wall Rebar Data” or “Design > Concrete Code Design > Beam/Column/Wall Design > [Update Rebar] button”

❗ 1. In this tutorial, “Modify Beam Rebar Data” will only be illustrated. In the same manner, Column and Wall Section Data can also be defined.

❗ 1. Rebar will be **MANUALLY** entered using “Design > Concrete Design Parameter > Modify Beam/Column/Wall Rebar Data”

❗ 1. Rebar can be **AUTOMATICALLY** entered using “Design > Concrete Code Design > Beam/Column/Wall Design > [Update Rebar] button” (this is illustrated later).

52
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Modify Beam Section Data (1)

**Modify Beam Rebar Data**

SECT: G1, G2, G3, G4, B1, WGI, WGI2

Element List: 11to356by69 12to357by69 13to358

Rebar Table:

Rebar	Top	Bottom	Stirrup	Size	Count	Spacing
Top	1	4		P25	2	
Bottom		2		P20	4	
Stirrup			2	P10		@ 100

Concrete Face to Center of Rebar (d<sub>t</sub>): 0.055 m

Options: ☐ Same Main Rebar Size at Top and Bottom, ☐ Same Main Rebar Size at I, M and J

1. Design > Concrete Design Parameter > Modify Beam Rebar Data...
2. SECT: check on ID "412".
3. Uncheck "Same Main Rebar Size at Top and Bottom" and "Same Main Rebar Size At I, M and J".
4. For Main Rebar at "End(I)"
5. For Top Rebar: in front of "Top" and "1" : "4" "P25"
6. Bottom Rebar: In front of "Bot" and "1" : "2" "P20"
7. For Main Rebar at "Center"
8. For Top Rebar: in front of "Top" and "1" : "2" "P20"
9. Bottom Rebar: In front of "Bot" and "1" : "4" "P25"
10. For Main Rebar at "Center"
11. For Top Rebar: in front of "Top" and "1" : "4" "P25"
12. Bottom Rebar: In front of "Bot" and "1" : "2" "P20"

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Modify Beam Section Data (2)

**Modify Beam Rebar Data**

SECT: G1, G2, G3, G4, B1, WGI, WGI2

Element List: 11to356by69 12to357by69 13to358

Rebar Table:

Rebar	Top	Bottom	Stirrup	Size	Count	Spacing
Top	1	4		P25	2	
Bottom		2		P20	4	
Stirrup			2	P10		@ 100

Concrete Face to Center of Rebar (d<sub>t</sub>, d<sub>b</sub>): 0.055 m

Options: ☐ Same Main Rebar Size at Top and Bottom, ☐ Same Main Rebar Size at I, M and J

13. Stirrup in "End(I)"
14. Arrangement: "2"
15. Stirrups Space: "100" mm
16. Stirrup in "Center"
17. Arrangement: "2"
18. Stirrups Space: "200" mm
19. Stirrup in "End(J)"
20. Arrangement: "2"
21. Stirrups Space: "100" mm
22. Stirrup: "P10"
23. d<sub>t</sub>, d<sub>b</sub> : 0.055m, 0.055m
24. Click [Add/Replace] Button

MIDAS Information Technology Co., Ltd.



midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### ULS Beam Member Code Check

**6-1. Beam Code Checking**

1. In this tutorial, only "Beam Code Checking" will be illustrated. In the same manner, Column/Wall Code Checking can be performed.

55
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Beam Code Checking (1)

1. Design > Concrete Code Check > Beam Checking...

2. Sorted by: Member

3. Results: Strength

4. Click to expand the dialog box.

5. SEL: MEMB "11"

Eurocode2:04 RC-Beam Checking Result Dialog

Code : Eurocode2:04 Unit : KN, m

Sorted by: ☒ Member ☐ Property ☐ Results ☐ Serviceability

Primary Sorting Option: ☐ SECT ☒ MEMB

MEMB	SECT	Span	Section	Bc	Hc	fyk	fk	POS	CHK	AsTop	AsBot	N(-) M <sub>Ed</sub>	LCB	N(-) M <sub>Rd</sub>	Rat-N	P(+) M <sub>Ed</sub>	LCB	P(+) M <sub>Rd</sub>	Rat-P	V <sub>Ed</sub>	LCB	V <sub>Rdc</sub>	Rat-V
11	G2	30000.0	I	OK	0.0020	0.0006	183.388	9	510.105	0.36	22.2076	11	170.404	0.13	99.0871	7	136.738	0.72					
412	G2	0.400 0.700 500000	M	OK	0.0006	0.0020	39.3944	11	170.404	0.23	43.9243	2	510.105	0.09	68.0898	3	136.738	0.50					
7.2000	G2	0.000 0.000 400000	J	OK	0.0020	0.0006	185.128	5	510.105	0.36	21.6764	13	170.404	0.13	99.6170	3	136.738	0.73					
12	G2	30000.0	I	OK	0.0020	0.0006	297.775	7	510.105	0.58	1.09638	11	170.404	0.01	130.488	5	136.738	0.95					
412	G2	0.400 0.700 500000	M	OK	0.0006	0.0020	49.6797	5	170.404	0.29	64.3412	6	510.105	0.13	110.663	3	136.738	0.81					
7.2000	G2	0.000 0.000 400000	J	OK	0.0020	0.0006	298.241	3	510.105	0.58	0.96975	13	170.404	0.01	130.604	9	136.738	0.96					
13	G2	30000.0	I	OK	0.0020	0.0006	158.255	6	510.105	0.31	0.91891	11	170.404	0.01	93.4868	6	136.738	0.68					
412	G2	0.400 0.700 500000	M	OK	0.0006	0.0020	16.0647	13	170.404	0.09	46.8231	8	510.105	0.09	61.9396	6	136.738	0.45					
7.2000	G2	0.000 0.000 400000	J	OK	0.0020	0.0006	154.394	2	510.105	0.30	2.04017	13	170.404	0.01	92.3795	2	136.738	0.68					
80	G2	30000.0	I	OK	0.0020	0.0006	174.498	9	510.105	0.34	32.2523	11	170.404	0.10	98.7432	7	136.738	0.72					
412	G2	0.400 0.700 500000	M	OK	0.0006	0.0020	40.3681	11	170.404	0.24	52.0411	2	510.105	0.10	68.1535	3	136.738	0.50					
7.2000	G2	0.000 0.000 400000	J	OK	0.0020	0.0006	177.574	5	510.105	0.35	31.3088	13	170.404	0.18	99.6807	3	136.738	0.73					
81	G2	30000.0	I	OK	0.0020	0.0006	282.763	7	510.105	0.55	14.2886	11	170.404	0.08	130.320	5	136.738	0.95					
412	G2	0.400 0.700 500000	M	OK	0.0006	0.0020	41.4967	11	170.404	0.24	79.4512	6	510.105	0.16	110.796	3	136.738	0.81					
7.2000	G2	0.000 0.000 400000	J	OK	0.0020	0.0006	283.573	3	510.105	0.56	14.0731	13	170.404	0.08	130.521	9	136.738	0.95					
82	G2	30000.0	I	OK	0.0020	0.0006	144.788	7	510.105	0.11	19.9874	11	170.404	0.06	94.6794	7	136.738	0.68					

Connect Model View: ☐ Select All ☐ Unselect ☐ Re-calc ☐ Summary...

Result View Option: ☒ All ☐ OK ☐ NG

Option for Detail Print Position: ☒ End 1. ☐ Mid. ☐ End 2. ☐ End 3.

Buttons:

56
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Beam Code Checking (2)

6. Click [Graphic...] button.

	END-1	END-2	END-3
(c) Load Combination No.	9	11	5
Moment (M <sub>Ed</sub> )	193.39	39.39	185.13
Strength (M <sub>Rd</sub> )	510.10	170.40	510.10
Check Ratio (M <sub>Ed</sub> /M <sub>Rd</sub> )	0.3993	0.2312	0.3629
(d) Load Combination No.	11	2	13
Moment (M <sub>Ed</sub> )	22.21	43.92	21.68
Strength (M <sub>Rd</sub> )	170.40	510.10	170.40
Check Ratio (M <sub>Ed</sub> /M <sub>Rd</sub> )	0.1303	0.0861	0.1272
Using Rebar Top (As <sub>Top</sub> )	0.0020	0.0006	0.0020
Using Rebar Bot (As <sub>Bot</sub> )	0.0006	0.0020	0.0006

	END-1	END-2	END-3
Load Combination No.	7	3	3
Factored Shear Force (V <sub>Ed</sub> )	99.09	65.09	99.62
Shear Strength by Conc (V <sub>RdC</sub> )	136.74	136.74	136.74
Using Shear Reinf. (As <sub>sw</sub> )	0.0016	0.0008	0.0016
Using Stirrup Spacing	2-F10 @100	2-F10 @200	2-F10 @100
Check Ratio	0.7246	0.4960	0.7285

57

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Beam Code Checking (3)

7. Option for Detail Print Position: check on "End I." "Mid." "End J."

8. Click [Detail...] button

LCB	C	Loadcase Name (Factor) + Loadcase Name (Factor) + Loadcase Name (Factor)
00033	1	1
00034	2	1
00035	3	1
00036	4	1
00037	5	1
00038	6	1
00039	7	1
00040	8	1
00041	9	1
00042	10	1
00043	11	1

58

MIDAS Information Technology Co., Ltd.





midas Gen Tutorial Eurocode Design of Multi-story RC Building

### Short/Long Term Elasticity Ratio

1. Design > Concrete Design Parameter > Modify Concrete Materials...
2. Select "C30/37" from Material List.
3. Click ... button.
4. Click [OK] button.
5. Click [Close] button.

61 MIDAS Information Technology Co., Ltd.

midas Gen Tutorial Eurocode Design of Multi-story RC Building

### Serviceability Load Combination Type

1. Design > General Design Parameter > Serviceability Load Combination Type...
2. Click [OK] button.

⚠ Once the load combinations are generated using "Auto Generation" as per Eurocode2 as in Step 3-1, the program automatically assigns the "Quasi-permanent", "Frequent" and "Characteristic" load combinations.

62 MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Automatic Rebar Input

1. Design > Concrete Code Design > Beam Design...

2. SEL: click [Select All] button.

3. Click [Update Rebar] button.

4. Click [Close] button.

1. By clicking [Update Rebar] button, the rebars designed in this dialog box will be automatically entered into the selected sections.

63
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### View Rebar Data on Section

1. Design > Concrete Design Parameter > Modify Beam Rebar Data...

2. SEL: check on ID "413".

3. Click [Close] button.

1. In this page, check the Rebar Data entered using [Update Rebar] in the previous page.

2. "In" signifies that Rebar are placed.

3. The entered Rebar Data are displayed.

64
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### Enter Serviceability Limit Control Parameters

1. Design > Concrete Design Parameter > Serviceability Parameters...
2. Option: Add/Replace
3. Selection Type: By Selection
4. Exposure Class: XD1
5. Stress Parameters- k1: 0.6, k2: 0.45, k3: 0.8, k4: 1
6. Quasi-permanent – Limit: 0.3 mm
7. Quasi-permanent Deflection Ctrl: L/250
8. Characteristic Deflection Control – Limit: L/250
9. Deflection Amplification Factor: 1
10. View > Select > Identity...
11. Select Type: Section
12. Select “411: G1”, “412: G2”, “413: G3”, “414: G4”, “415: B1”, “421: WG1”, “422: WG2”
13. Click [Add] Button.
14. Click [Close] Button.
15. Click [Apply] Button.

65
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial
Eurocode Design of Multi-story RC Building

### SLS Checks

#### Serviceability Checking for Concrete Beam

1. Serviceability check is provided for Beam members for the following limit states.

- Stress limitation
- Crack control
- Deflection control

66
MIDAS Information Technology Co., Ltd.

midas Gen Tutorial

Eurocode Design of Multi-story RC Building

### Serviceability Checking (1)

1. Design > Concrete Code Check > Beam Checking...
2. Sorted by: Member
3. Results: Serviceability
4. Click to expand the dialog box.
5. SEL: select MEMB "1"

MIDAS Information Technology Co., Ltd.

midas Gen Tutorial

Eurocode Design of Multi-story RC Building

### Serviceability Checking (2)

6. Click [Graphic...] button.

MIDAS Information Technology Co., Ltd.

### Serviceability Checking (3)

7. Click [Detail...] button.

```

02042
02043
02044
02045
02046
02047
02048
02049
02050
02051
02052
02053
02054
02055
02056
02057
02058
02059
02060
02061
02062
02063
02064
02065
02066
02067
02068
02069
02070
02071
02072
02073
02074
02075
02076
02077
02078
02079
02080
02081
02082
02083
02084
02085
02086
02087
02088
02089
02090
02091
02092
02093
02094
02095
02096
02097
02098
02099
02100
02101
02102
02103
02104
02105
02106
02107
02108
02109
02110
02111
02112
02113
02114
02115
02116
02117
02118
02119
02120
02121
02122
02123
02124
02125
02126
02127
02128
02129
02130
02131
02132
02133
02134
02135
02136
02137
02138
02139
02140
02141
02142
02143
02144
02145
02146
02147
02148
02149
02150
02151
02152
02153
02154
02155
02156
02157
02158
02159
02160
02161
02162
02163
02164
02165
02166
02167
02168
02169
02170
02171
02172
02173
02174
02175
02176
02177
02178
02179
02180
02181
02182
02183
02184
02185
02186
02187
02188
02189
02190
02191
02192
02193
02194
02195
02196
02197
02198
02199
02200
02201
02202
02203
02204
02205
02206
02207
02208
02209
02210
02211
02212
02213
02214
02215
02216
02217
02218
02219
02220
02221
02222
02223
02224
02225
02226
02227
02228
02229
02230
02231
02232
02233
02234
02235
02236
02237
02238
02239
02240
02241
02242
02243
02244
02245
02246
02247
02248
02249
02250
02251
02252
02253
02254
02255
02256
02257
02258
02259
02260
02261
02262
02263
02264
02265
02266
02267
02268
02269
02270
02271
02272
02273
02274
02275
02276
02277
02278
02279
02280
02281
02282
02283
02284
02285
02286
02287
02288
02289
02290
02291
02292
02293
02294
02295
02296
02297
02298
02299
02300
02301
02302
02303
02304
02305
02306
02307
02308
02309
02310
02311
02312
02313
02314
02315
02316
02317
02318
02319
02320
02321
02322
02323
02324
02325
02326
02327
02328
02329
02330
02331
02332
02333
02334
02335
02336
02337
02338
02339
02340
02341
02342
02343
02344
02345
02346
02347
02348
02349
02350
02351
02352
02353
02354
02355
02356
02357
02358
02359
02360
02361
02362
02363
02364
02365
02366
02367
02368
02369
02370
02371
02372
02373
02374
02375
02376
02377
02378
02379
02380
02381
02382
02383
02384
02385
02386
02387
02388
02389
02390
02391
02392
02393
02394
02395
02396
02397
02398
02399
02400
02401
02402
02403
02404
02405
02406
02407
02408
02409
02410
02411
02412
02413
02414
02415
02416
02417
02418
02419
02420
02421
02422
02423
02424
02425
02426
02427
02428
02429
02430
02431
02432
02433
02434
02435
02436
02437
02438
02439
02440
02441
02442
02443
02444
02445
02446
02447
02448
02449
02450
02451
02452
02453
02454
02455
02456
02457
02458
02459
02460
02461
02462
02463
02464
02465
02466
02467
02468
02469
02470
02471
02472
02473
02474
02475
02476
02477
02478
02479
02480
02481
02482
02483
02484
02485
02486
02487
02488
02489
02490
02491
02492
02493
02494
02495
02496
02497
02498
02499
02500
02501
02502
02503
02504
02505
02506
02507
02508
02509
02510
02511
02512
02513
02514
02515
02516
02517
02518
02519
02520
02521
02522
02523
02524
02525
02526
02527
02528
02529
02530
02531
02532
02533
02534
02535
02536
02537
02538
02539
02540
02541
02542
02543
02544
02545
02546
02547
02548
02549
02550
02551
02552
02553
02554
02555
02556
02557
02558
02559
02560
02561
02562
02563
02564
02565
02566
02567
02568
02569
02570
02571
02572
02573
02574
02575
02576
02577
02578
02579
02580
02581
02582
02583
02584
02585
02586
02587
02588
02589
02590
02591
02592
02593
02594
02595
02596
02597
02598
02599
02600
02601
02602
02603
02604
02605
02606
02607
02608
02609
02610
02611
02612
02613
02614
02615
02616
02617
02618
02619
02620
02621
02622
02623
02624
02625
02626
02627
02628
02629
02630
02631
02632
02633
02634
02635
02636
02637
02638
02639
02640
02641
02642
02643
02644
02645
02646
02647
02648
02649
02650
02651
02652
02653
02654
02655
02656
02657
02658
02659
02660
02661
02662
02663
02664
02665
02666
02667
02668
02669
02670
02671
02672
02673
02674
02675
02676
02677
02678
02679
02680
02681
02682
02683
02684
02685
02686
02687
02688
02689
02690
02691
02692
02693
02694
02695
02696
02697
02698
02699
02700
02701
02702
02703
02704
02705
02706
02707
02708
02709
02710
02711
02712
02713
02714
02715
02716
02717
02718
02719
02720
02721
02722
02723
0
```

### Serviceability Checking (4)

8. Click **[Summary...]** button.

```

MIDAS/Text Editor [Untitled.rpt]
File Edit View Window Help

[Icons]

00001      18 2      DL( 1.000) +      LL( 1.000) +      WT(-0.600)
00002      19 2      DL( 1.000) +      LL( 0.700) +      WC( 1.000)
00003      20 2      DL( 1.000) +      LL( 0.700) +      WT( 1.000)
00004      21 2      DL( 1.000) +      LL( 0.700) +      WC(-1.000)
00005      22 2      DL( 1.000) +      LL( 0.700) +      WT(-1.000)
00006      23 2      DL( 1.000) +      LL( 0.500)
00007      24 2      DL( 1.000) +      LL( 0.300) +      WC( 0.200)
00008
00009
00010      aidas Gen - RC-Beam Checking [ Eurocode2:04 ]      Gen 2010
00011
00012      -----
00013      25 2      DL( 1.000) +      LL( 0.300) +      WT( 0.200)
00014      26 2      DL( 1.000) +      LL( 0.300) +      WC(-0.200)
00015      27 2      DL( 1.000) +      LL( 0.300) +      WT(-0.200)
00016      28 2      DL( 1.000) +      LL( 0.300)
00017
00018
00019      aidas Gen - RC-Beam Checking [ Eurocode2:04 ]      Gen 2010
00020
00021      -----
00022      *.PROJECT : KM, aa
00023
00024      [ Eurocode2:04 ] RC-BEAM CHECK SUMMARY SHEET --- SELECTED MEMBERS IN ANALYSIS MODEL.
00025
00026
00027
00028      *.MEMB = 1, SECT = 411 (G1, RECT), Span = 10200.0
00029      *.Ec = 400.00, Rc = 700.00
00030      *.ck = 0.03000, f_yk = 0.50000, f_yw = 0.40000
00031
00032
00033      POS CKR AsTop AsBot StrCon( LCB) RatSCStrSCsl( LCB) RatSCSl Crack( LCB) RatC( Disp.( LCB) RatD
00034
00035      I 5399.6 942.48 17.7191( 18) 0.511510.7971 18) 0.25910.05901 28) 0.1971
00036      M 626.32 3436.1 0.00000 28) 0.00000 28) 0.00000 28) ****10.00001 28) ****13.5724( 16) 0.098
00037      I 5399.6 942.48 10.0961( 15) 0.540191.3931 16) 0.27310.0636 28) 0.2121
00038
00039
00040
00041
00042
00043
00044
00045
00046
00047
00048
00049
00050
00051
00052
00053
00054
00055
00056
00057
00058
00059
00060
00061
00062
00063
00064
00065
00066
00067
00068
00069
00070
00071
00072
00073
00074
00075
00076
00077
00078
00079
00080
00081
00082
00083
00084
00085
00086
00087
00088
00089
00090
00091
00092
00093
00094
00095
00096
00097
00098
00099
00100
00101
00102
00103
00104
00105
00106
00107
00108
00109
00110
00111
00112
00113
00114
00115
00116
00117
00118
00119
00120
00121
00122
00123
00124
00125
00126
00127
00128
00129
00130
00131
00132
00133
00134
00135
00136
00137
00138
00139
00140
00141
00142
00143
00144
00145
00146
00147
00148
00149
00150
00151
00152
00153
00154
00155
00156
00157
00158
00159
00160
00161
00162
00163
00164
00165
00166
00167
00168
00169
00170
00171
00172
00173
00174
00175
00176
00177
00178
00179
00180
00181
00182
00183
00184
00185
00186
00187
00188
00189
00190
00191
00192
00193
00194
00195
00196
00197
00198
00199
00200
00201
00202
00203
00204
00205
00206
00207
00208
00209
00210
00211
00212
00213
00214
00215
00216
00217
00218
00219
00220
00221
00222
00223
00224
00225
00226
00227
00228
00229
00230
00231
00232
00233
00234
00235
00236
00237
00238
00239
00240
00241
00242
00243
00244
00245
00246
00247
00248
00249
00250
00251
00252
00253
00254
00255
00256
00257
00258
00259
00260
00261
00262
00263
00264
00265
00266
00267
00268
00269
00270
00271
00272
00273
00274
00275
00276
00277
00278
00279
00280
00281
00282
00283
00284
00285
00286
00287
00288
00289
00290
00291
00292
00293
00294
00295
00296
00297
00298
00299
00300
00301
00302
00303
00304
00305
00306
00307
00308
00309
00310
00311
00312
00313
00314
00315
00316
00317
00318
00319
00320
00321
00322
00323
00324
00325
00326
00327
00328
00329
00330
00331
00332
00333
00334
00335
00336
00337
00338
00339
00340
00341
00342
00343
00344
00345
00346
00347
00348
00349
00350
00351
00352
00353
00354
00355
00356
00357
00358
00359
00360
00361
00362
00363
00364
00365
00366
00367
00368
00369
00370
00371
00372
00373
00374
00375
00376
00377
00378
00379
00380
00381
00382
00383
00384
00385
00386
00387
00388
00389
00390
00391
00392
00393
00394
00395
00396
00397
00398
00399
00400
00401
00402
00403
00404
00405
00406
00407
00408
00409
00410
00411
00412
00413
00414
00415
00416
00417
00418
00419
00420
00421
00422
00423
00424
00425
00426
00427
00428
00429
00430
00431
00432
00433
00434
00435
00436
00437
00438
00439
00440
00441
00442
00443
00444
00445
00446
00447
00448
00449
00450
00451
00452
00453
00454
00455
00456
00457
00458
00459
00460
00461
00462
00463
00464
00465
00466
00467
00468
00469
00470
00471
00472
00473
00474
00475
00476
00477
00478
00479
00480
00481
00482
00483
00484
00485
00486
00487
00488
00489
00490
00491
00492
00493
00494
00495
00496
00497
00498
00499
00500
00501
00502
00503
00504
00505
00506
00507
00508
00509
00510
00511
00512
00513
00514
00515
00516
00517
00518
00519
00520
00521
00522
00523
00524
00525
00526
00527
00528
00529
00530
00531
00532
00533
00534
00535
00536
00537
00538
00539
005
```